WATE	R WEI	LL RECORD	Form WV	WC-5	Division of Wate	er Resources App. N	lo. L
1 LOCATION OF WATER WELL: County: Ellsworth		Fraction 1/4 SE 1/4 SE	1/2 NF 1/4	Section Number	Township No. T 16 S		
		Address of Well Location; i		Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)		
3S, 2E of Ellsworth, Ks					Longitude: (in decimal degrees)		
					Elevation:		
2 WATER WELL OWNER: Lloyd Prohaska					Datum: WGS 84, NAD 83, NAD 27		
RR#, Street Address, Box #: 1675 Ave O					Collection Method: GPS unit (Make/Model:)		
Gir Grand Gir			h, KS 67439		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
					Est. Accuracy: -		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 97 ft.							
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1),60 ft. (2), ft. (3), (3), (3)							(2) #
SECTION BOX: Depth(s) Groundwater Encountered (1).60							lav/vr 07/22/14
		Pump	test data: Well water	ft. after	ft. after hours pumping gpm		
N	w N	POT VIELD 19	gpm. Well water wasft. after hours pumping gpm				
w	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Bore Hole Diam	eterin. to		ft., andin.	to	
			TO BE USED AS:				Injection well
sv	sw -sE						
	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well stock						
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No If yes, mo/day/yr sample was submitted							
mile Water well disinfected?							
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other							
Casing diameter .5							
Casing height above land surface. 12. in., Weight 2.8. lbs./ft., Wall thickness or gauge No. Sch. 40.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Continuous stot Mili stot Gauze wrapped Torch cut Drifted notes None (open note) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
Fromft. to							
GRAVEL PACK INTERVALS: From							
From							
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other							
Grout Intervals: From .0							
Septic tank							
Sewer lines							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well East ☐ Distance from well .75.							
	TO TO		101.00				
FROM 0	2	LITHOLOG	IC LOG	FROM	TO LITHO, LO	JG (cont.) or PLU	IGGING INTERVALS
2	7	top soil					1104
7	20	clay sand and gravel				- Transition	
20	80	shale					
80	97	sand rock shale botto	m			7110	
-							
							V-11
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .07/22/14 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 186							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to							
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							

http://www.kdheks.gov/waterwell/index.html