

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Ellsworth		NE ¼ NW ¼ NW ¼		11		T 17 S		R 10 E/W	
Distance and direction from nearest town or city street address of well if located within city?									
Approximately ½ mile north and ¼ mile east of Holyrood									
2 WATER WELL OWNER:		John Phelan							
RR#, St. Address, Box # :		P.O. Box 56							
City, State, ZIP Code :		Holyrood, KS 67450							
		Board of Agriculture, Division of Water Resources							
		Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 82 ft. ELEVATION: unknown							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 17.5 ft. below land surface measured on mo/day/yr 10-15-97							
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm							
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 10 in. to 80 ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes ☒ No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No. .214									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 25 ft. to 50 ft., From ft. to ft.									
From 55 ft. to 80 ft., From ft. to ft.									
6 GROUT MATERIAL: Dirt ¹ Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug									
Grout Intervals: From 0 ft. to 5 ft., From 5 ft. to 25 ft., From 50 ft. to 55 ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None known									
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	6	Topsoil							
6	20	Clay, brown							
20	70	Clay, brown, soft							
70	75	Clay							
75	80	Broken limestone gravel							
80		Dakota shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-15-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 10-21-97 under the business name of Clarke Well & Equipment, Inc. by (signature)									