

08-69

1 LOCATION OF WATER WELL: County: ELLISWORTH	Fraction SW 1/4 NW 1/4 SW 1/4	Section Number 30	Township Number T 17 S	Range Number R 10 EW
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

7777 AVE. Y

2 WATER WELL OWNER: KN PROCESSING, INC.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: R.R. 1 BOX 5A	Application Number:
City, State, ZIP Code: BUSHTON, KS. 67427	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 23 ft. ELEVATION:
--	---

1 Mile

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: **7 1/4** in. to **23** ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		☒ Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
☒ PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: 2 in. to 13 ft. Dia in. to ft. Dia in. to ft.			Threaded
Casing height above land surface: 32 in. weight Sched 40 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	☒ Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 23 ft. to 13 ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 23 ft. to 10 ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ Bentonite	4 Other
Grout Intervals: From ft. to ft. From 10 ft. to 10 ft. From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	☒ Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? SE			How many feet? 1200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	SANDY CLAY, REDDISH BRN			
3	10	SANDY SILT, REDDISH YELLOW			
10	11	SILTY SAND, REDDISH YELLOW			
11	16	SANDY CLAY, REDDISH YELLOW			
16	19	SANDY CLAY, OK BRN			
19	22	SILTY SAND, OK BRN			
22	23	SILTY SAND, BROWN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-18-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 6-5-97 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature) <i>[Signature]</i>
--