

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ellsworth		SE 1/4 NW 1/4 SE 1/4	27	T 17 S	R 10 E (W)
Distance and direction from nearest town or city street address of well if located within city? 3 S. of Hollyrood, KS					
2 WATER WELL OWNER: Harlem Boye					
RR#, St. Address, Box # :		425 Smith Dr.		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Colby, KS. 67701		Application Number: T90- 0221	
3 LOCATE WELL'S LOCATION WITHIN AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 143 ft. ELEVATION:			
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 78 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot X 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No. X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X ... Clamped
X 2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter ... 5 in. to ... 123 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface ... 12 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		X 3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From ... 123 ft. to ... 143 ft., From ft. to ft.					
From ... 20 ft. to ... 143 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ... 20 ft. to ... 143 ft., From ft. to ft.					
From ... 20 ft. to ... 143 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X 3 Bentonite 4 Other					
Grout Intervals: From ... 0 ft. to ... 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	none
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	78	Clay			
78	143	Sandstone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 6/5/90 ... and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. ... 4628 ... This Water Well Record was completed on (mo/day/yr) ... 7/4/90 ...					
under the business name of Sam's Water Well Service by (signature) <i>Sam's Water Well Service</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					