

1 LOCATION OF WATER WELL: County: <u>Elksworth</u>	Fraction <u>SW 1/4 SE 1/4 SW 1/4</u>	Section Number <u>33</u>	Township Number <u>T 17 S</u>	Range Number <u>R 10 E</u>
---	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

4 miles east of Clapham, KS

2 WATER WELL OWNER: <u>William Stumps</u>	<u>Red Tiger Drly Co</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>R70</u>	<u>1720 N St Bldg</u>	Application Number: <u>900065</u>
City, State, ZIP Code: <u>Bushton, KS</u>	<u>Wichita, KS 67202</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>130</u> ft. ELEVATION:
--	--

1 Mile

Depth(s) Groundwater Encountered 1. 30 ft. 2. 2-23-90 ft. 3. 2-23-90 ft.

WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 30 ft. after 2-23-90 hours pumping 30 gpm

Est. Yield 30 gpm: Well water was 30 ft. after 2-23-90 hours pumping 30 gpm

Bore Hole Diameter was 30 in. to 30 ft., and 30 in. to 30 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5</u> in. to <u>3</u> ft., Dia <u>3</u> in. to <u>3</u> ft., Dia <u>3</u> in. to <u>3</u> ft.			
Casing height <u>above</u> land surface <u>3' below</u> in., weight <u>3</u> lbs./ft. Wall thickness or gauge No. <u>3</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify)
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel		12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>3</u> ft. to <u>130</u> ft., From <u>3</u> ft. to <u>130</u> ft., From <u>3</u> ft. to <u>130</u> ft.		
GRAVEL PACK INTERVALS:	From <u>3</u> ft. to <u>130</u> ft., From <u>3</u> ft. to <u>130</u> ft., From <u>3</u> ft. to <u>130</u> ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From <u>3</u> ft. to <u>130</u> ft., From <u>3</u> ft. to <u>130</u> ft., From <u>3</u> ft. to <u>130</u> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well Gas well
			13 Insecticide storage	16 Other (specify below)
Direction from well?			How many feet?	<u>100' NE</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>3'</u>	<u>130'</u>	<u>Cement</u>			
<u>0</u>	<u>3'</u>	<u>soil</u>			
		<u>Filled entire well with cement</u>			
		<u>Cut casing off 3' below ground level</u>			
		<u>filled with surface silts from 3' below to ground level</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-23-90</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>2-24-90</u> This Water Well Record was completed on (mo/day/yr) <u>2-24-90</u> under the business name of <u>Red Tiger Drly Co</u> by (signature) <u>Clay Engel</u>
