

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

WW090809

1 LOCATION OF WATER WELL: County: Barton Fraction SW 1/4 NE 1/4 NW 1/4 Section Number 22 Township Number T 17 S Range Number R 12

Distance and direction from nearest town or city street address of well if located within city? 2 1/2 North, 5 1/8 West of Claflin Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Larry Jenisch RR#, St. Address, Box #: 810 Houston City, State, ZIP Code: Claflin, Ks. 67525

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 2x2 grid with 'X' in the NW quadrant] 4 DEPTH OF COMPLETED WELL: 95 ft. Depth(s) Groundwater Encountered (1) 33 ft. (2) 2-3-10 ft. (3) 2-3-10 ft. WELL'S STATIC WATER LEVEL: 33 ft. below land surface measured on mo/day/yr... 2-3-10 Pump test data: Well water was... Est. Yield: N/A gpm: Well water was... WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specify below) 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 10 Monitoring well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) Stock Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted Water well disinfected? Yes HTH No

5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 5 in. to 55 ft., Diameter 24 in. to 55 ft., Diameter Casing height above land surface 24 in., Weight SDR-26 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 95 ft. to 55 ft. GRAVEL PACK INTERVALS: From 95 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug Grout Intervals: From 20 ft. to 0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 15 Oil well/gas well None 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage

Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 9 Yellow Shale 9 39 Dk gray shale 39 58 Dk gray shale/ hard sandstone 58 70 Dk gray shale 70 85 Soft sandstone 85 87 Lt gray shale 87 92 Sandstone 92 95 Dk gray shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-4-10 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 3-10-10 under the business name of Rosencrantz-Bemis by (signature) Sara Albit

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.