


1 LOCATION OF WATER WELL: Fraction C 1/4 SW 1/4 SW 1/4 Section Number 33 Township Number T 17 S Range Number R 13 E/W
 County: Barton

Distance and direction from nearest town or city street address of well if located within city?
Hoisington & K-4 Susan Road 1/4 mi North East into

2 WATER WELL OWNER: Hoisington USD 431 Well # 3
 RR#, St. Address, Box # : Activity Center
 City, State, ZIP Code : Hoisington ks 67544
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 180 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 160 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 65 ft. below land surface measured on mo/day/yr 10-14-03
 Pump test data: Well water was 170 ft. after 8 hours pumping 60 gpm
 Est. Yield 60 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected YES No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 140 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 20 in., weight 520 40 lbs./ft. Wall thickness or gauge No. SQR-31
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass XPVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot X Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 140 ft. to 180 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 130 ft. to 180 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite 4 Other
 Grout intervals: From 130 ft. to 0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Compact Clay			
3	6	Black Soil			
6	20	yellow clay			
20	40	Red sandstone fine sand			
40	120	Red clay			
120	150	Blue shale			
150	160	Red & white shale			
160	175	Med Red & Brown sand soft			
175	180	Red shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was As constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-15-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 660 This Water Well Record was completed on (mo/day/yr) 10-15-03 under the business name of Goodman Waterwell Org by (signature) Jak Hood