					Well#2			
WATER WELL RECORD			Form WV	VC-5		r Resources App. N		
Co	unty: Bart	OF WATER WELL:	1/4 SE 1/4 SE		Section Number 28	T 17 S	Range Number R 14 □E ☑W	
	Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:			
fro	from nearest town or intersection: If at owner's address, check here				Latitude:			
1	1 1/4 North, 3 East of Olmitz							
					Elevation:			
2 W	- Indinas Laison				Collection Method: ☐ GPS unit (Make/Model:			
RR#, Street Address, Box #: 562 W Stat City, State, ZIP Code : Olmitz, KS			State Road 4 KS 67564					
	SECTION BOX: Denth(s) Groundwater Encountered (1)							
-	N WELL'S STATIC WATER LEVEL4/ft. below land surface measured on mo/day/yr6-26-13							
Pump test data: Well water wasft. after hours						hours pum	ping gpm	
	EST. YIELD. N/A gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to .80 ft., and in. to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
w								
	SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well							
L.,	Was a chemical/bacteriological sample submitted to Department? Yes V No							
	S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: M Glued Clamped Welded Threaded								
Casing diameter .5 in. to .80 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface18								
IYPI	E OF SCRE	Stainless Steel	PVC		Other (Specify)		İ	
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
From								
	GRAV	EL PACK INTERVALS:	From 80 fi	t to 20	ft., From	ft.	to ft.	
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 20 ft., From ft. to ft.								
	Intervals:	From ft. to	ft., From	.20	ft. to .Y ft.,	From	. ft. toft.	
		est source of possible control	imination:	□ Livestock •	ans Insecticide	storage M Oth	er (specify below)	
Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
		ht sewer lines 🔲 Seepage p		Fertilizer si	orage 🔲 Oil well/ga		9	
Direction from well								
FROM		LITHOLOG	IC LOG	FROM	TO LITHO. L	OG (cont.) or PLU	GGING INTERVALS	
0	4	Top soil						
14	14 22	Brown clay						
22	56	Yellow clay & sandstor Light gray shale	10					
56	80	Sandstone/ shale strea	ks					
55		Januarana, andro andro						
						- · · · · · · · · · · · · · · · · · · ·		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .9-3-13								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 9-12-13								
under the business name of Rosencrantz-Bemis Ent Inc. by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at								
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								