	WATER W	ELL RECORD For	n WWC-5 K	SA 82a-1212	ID No. MW - 6	
1 LOCATION OF WATER WELL:	Fraction			Number	Township Number	Range Number
County: Rush	SE 1/4 S	SE 1/4 SE	1/4 2	6	т 17 s	R 16W EW
Distance and direction from nearest tow	n or city street address	of well if located wi	thin city?			
2 WATER WELL OWNER: Norman Stieben						
RR#, St. Address, Box # : PO Box					Board of Agriculture Div	ision of Water Resources
City State ZIP Code . Otis. K	S 67565				Application Number:	ision of water resources
2 LOCATE WELL'S LOCATON WITH		,				
AN "X" IN SECTION BOX:	DEPTH OF COMP	PLETED WELL	29.81	ft. ELEVATI	ION:	
N	Depth(s) Groundwate	r Encountered 1		ft. 2	ft.	3 ft.
	WELL'S STATIC WAT	TER LEVEL 1	9.43 ft. belo	ow land surfa	ce measured on mo/day	/yr 10-19-06
NW NE						oumpinggpm
	Est. Yield	gpm: Well water v	was	ft. af	ter hours	oumpinggpm
₹ W E	Bore Hole Diameter	in. to	29.81	ft. 8	and in	n. to ft. 1 Injection well
			Helu water supp	JIY .	1 Dewatering	2 Other (Specify below)
swse	2 Irrigation 4	Industrial 7 Lav	wn and garden ((domestic)	10 Monitoring well	
	Was a chemical/bacte	riological sample su	bmitted to Depa	artment? Yes	No X If yes	, mo/day/yr sample was
S	submitted				Nell Disinfected? Yes	
5 TYPE OF BLANK CASING USED:		Wrought Iron	8 Concrete t	ile	CASING JOINTS: Glue	d Clamped
Steel 3 RMP (SR) 6	Asbestos-Cement	9 Other (spe	cify below)	Wek	led
2 PVC 4 ABS		Fiberglass			Thre	aded X
Blank casing diameter 2	in. to 14.81	A Dia	A		Die	in. to ft.
Casing height above land surface TYPE OF SCREEN OR PERFORATION	0 in., v	eight	716	lbs./ft. Wa	Il thickness or gauge No.	.154
TYPE OF SCREEN OR PERFORATION	N MATERIAL:	F16	PV	0	10 Asbestos-ceme	ent
1 Steel 3 Stainle 2 Brass 4 Galvar	nized steel 6	Concrete tile	8 KM	P (SR)	11 Other (specify)	on holo)
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4	Key punched	7 Torch	cut	10	Other (specify)	
SCREEN-PERFORATED INTERVALS:		1 ft. to	29.81	ft. From	ft. 1	to ft.
	From	ft. to		ft. From	ft. :	toft.
GRAVEL PACK INTERVALS:	From 12.8					toft.
	From	ft. to		ft. From	ft.	to ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals From 0 ft. to 1 ft. From 1 ft. to 12.81 ft. From ft. to ft.						
What is the nearest source of possible of	contamination:		1	0 Livestock	pens 14 Ab	andoned water well
		7 Pit privy		1 Fuel store	•	well/ Gas well
2 Sewer lines	5 Cess pool	8 Sewage la	-	2 Fertilizer		her (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site Direction from well? How many feet?						
FROM TO CODE	LITHOLOGIC	CLOG	FROM	TO TO	PLUGGING II	NTERVALS
0 13 Bro	own Fat Clay					
13 30 Ye	llowish – Brown	Lean Clay				
			<u> </u>			
	····		 			
			 			· · · · · · · · · · · · · · · · · · ·

7 CONTRACTOR'S OR LANDOWNER	R'S CERTIFICATION:	This water well was	(1) constructed,	(2) reconstru	cted, or (3) plugged unde	r my jurisdiction and was
completed on (mo/day/yr) 10-19-06 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No.	5	54	This Wate	r Well Recon	d was completed on (mo	
under the husiness name of	Wooffer F	Pump & Well Ir	1C.	by (si	ignature) bus (Worte
INSTRUCTIONS:, Please fill in blanks Jackson St., Ste. 420, Topeka, Kansa	s and circle the correct ar	nswers. Send three co	pies to Kansas D	Department of	Health and Briviropment, B	ureau of Water, 1000 S W
Jackson St., Sta. 420, Topera, Kansa	a voo (2-130/. Telephon	o. 810-280-0040. Se	IN OR TO WATE	K WELL OWN	IER and retain one for your	records.