WATE	R WEI	LL RECORD	Form WV	VC-5	Division of Water Resources App. No.		
II.	ATION ity: Rus	OF WATER WELL:	Fraction ¹ / ₄ NE ¹ / ₄ SW	¼ SW ¼	Section Number Township No. Range Number 35 T 17 S R 17 DE [7 IW	
		Address of Well Location; i			Global Positioning System (GPS) information:		
		town or intersection: If at o			Latitude:	rees)	
1	of Bison		,, ,,		Longitude: (in decimal degr		
'-	ווטפום וכ	, NO			Elevation:	,	
		DI I OITINDD			<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27		
		ELL OWNER: John Lo			Collection Method:		
RR#, Street Address, Box #: 3224 CR320 City, State, ZIP Code : Bison, KS 67520				GPS unit (Make/Model:			
City	, State, Z	IP Code : Bison, K	S 67520		Digital Map/Photo, Topographic Map, Land Sur	vey	
3 LOC	ATE WE	T T			Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m		
	H AN "X	" IN 4 DEPTH OF C	COMPLETED WELL	213	ft		
I .	TION BC						
	N WELL'S STATIC WATER LEVEL125ft. below land surface measured on mo/day/yr. 8/23/11						
Pump test data: Well water wasft. after hours pumpinggr						epm	
EST. YIELD.15gpm. Well water was					ft. after hours pumpingg	pm	
w NY	w						
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well							
Demostic Decodlet Delifield water supply Dewatering Dethar (Specify below)							
Irrigation Industrial Domestic-lawn & garden Monitoring well							
	Was a chemical/bacteriological sample submitted to Department? Yes V No						
S If yes, mo/day/yr sample was submitted							
mile Water well disinfected? ☑ Yes □ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .5 in. to .113 ft., Diameter .8 in. to .79 ft., Diameter in. to ft.							
Casing height above land surface 12 in., Weight 2.8 lbs./ft., Wall thickness or gauge No. Sch. 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ✔ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)							
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From							
Fromft. toft., Fromft. toft.							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other							
					it. to it., Pioni it. to		
What is the nearest source of possible contamination: Septic tank							
	Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
	Watertig	ht sewer lines		Fertilizer st	torage Oil well/gas well metal shed		
Direc	ction from	n well North	······	Distance	from well68.		
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERV	ALS	
0	2	top soil			Note:		
2	40	clay			Drilled 12 3/4" hole to 79'.		
40	45	coarse sand and grave			Set 8" surface pipe to 79'		
45	75	clay					
75	125	shale					
125	213	sand rock with shale st	reaks				
	1						
	<u> </u>						
	†		."				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .08/23/.11 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mg/day/year) .98/27/11							
under the business name of Kelly's Water Well Service, Inc. by (signature) Kathum L. Hoad							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-	-1212				Check: White Copy, Blue Copy, Pink	(Copy	