

1] LOCATION OF WATER WELL: County: Rush	Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 33	Township Number T 17 S	Range Number R 17 E
---	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

101 North Main, Bison, Kansas MW#1

2] WATER WELL OWNER: Mid-State Coop RR#, St. Address, Box # : 101 North Main City, State, ZIP Code : Bison, Kansas	Board of Agriculture, Division of Water Resources Application Number:
---	--

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4] DEPTH OF COMPLETED WELL 59.0 ft. ELEVATION: 44 ft. Depth(s) Groundwater Encountered 1. 43 ft. 2. 44 ft. 3. 12-11-92 ft. WELL'S STATIC WATER LEVEL 43 ft. below land surface measured on mo/day/yr Pump test data: Well water was 7 7/8 in. to 59.0 ft. after 7 7/8 hours pumping 59.0 gpm Est. Yield 7 7/8 gpm: Well water was 7 7/8 ft. after 7 7/8 hours pumping 59.0 gpm Bore Hole Diameter 7 7/8 in. to 59.0 ft. and 59.0 in. to 59.0 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted 12-11-92 Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
---	--

5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input type="checkbox"/> Clamped <input type="checkbox"/> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <input type="checkbox"/> 7 Fiberglass Threaded <input checked="" type="checkbox"/>	Blank casing diameter 2 in. to 39 ft. Dia 39 in. to 39 ft. Dia 39 in. to 39 ft. Casing height above land surface 0 in. weight 0 lbs./ft. Wall thickness or gauge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7 PVC SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)	SCREEN-PERFORATED INTERVALS: From 39.0 ft. to 59.0 ft. From 39.0 ft. to 59.0 ft. GRAVEL PACK INTERVALS: From 37.0 ft. to 59.0 ft. From 37.0 ft. to 59.0 ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	GROUT INTERVALS: From 0 ft. to 35.5 ft. From 35.5 ft. to 37 ft. From 37 ft. to 37 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	Direction from well? northwest How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8"	concrete			
8"	5'	clay, drk. brown			
5'	12'	silty clay, brown			flush mount cover
12	22	silty clay, red brown			KDHE ID # 00092658
22	45	silty clay, brown			
45	59	very silty clay, brown			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-16-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12-28-92 under the business name of GeoCore Services, Inc. by (signature) Doug Ray
--