

1 LOCATION OF WATER WELL: County: Rush	Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 33	Township Number T 17 S	Range Number R 17 EW
--	----------------------------------	-----------------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

101 North Main, Bison, Kansas MW#2

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	Mid-State Coop 101 North Main Bison, Kansas	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 58.9 ft. ELEVATION: 45 ft.
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 43 ft. below land surface measured on mo/day/yr 12-11-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 7/8 in. to 58.9 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <input checked="" type="checkbox"/>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 38.9 ft., Dia in. to ft., Dia in. to ft.			Threaded <input checked="" type="checkbox"/>
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 38.9 ft. to 58.9 ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	From 37 ft. to 58.9 ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 37 ft., From 37 ft. to 39 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage
Direction from well? south				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8"	asphalt			
8"	5'	dark brown clay			flush mount cover
5'	10'	medium brown clay			KDHE ID # 00091532
10'	22'	red brown clay, silty			
22'	35'	medium to light brown clay, very silty			
35'	45'	red brown clay, silty			
45'	59'	brown clay and silty, trace sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-16-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12-28-92 under the business name of GeoCore Services, Inc. by (signature) <i>Doug Ray</i>
