


1 LOCATION OF WATER WELL: County: Rush Fraction SE 1/4 NE 1/4 SE 1/4 Section Number 33 Township Number T 17 S Range Number R 18 EW

Distance and direction from nearest town or city street address of well if located within city?

521 Main Street, LaCrosse, Kansas

2 WATER WELL OWNER: Craig Janousek  
 RR#, St. Address, Box #: 521 Main Street Board of Agriculture, Division of Water Resource  
 City, State, ZIP Code: LaCrosse, Ks. 67548 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: 35 ft.  
 Depth(s) Groundwater Encountered 1. 13.71 ft. 2. 35 ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 13.71 ft. below land surface measured on mo/day/yr 10-12-93  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 7.5/8 in. to 38 ft., and in. to ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
 2 PVC 4 ABS 7 Fiberglass Threaded X  
 Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 13 ft. to 38 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 11 ft. to 38 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 9 ft., From 9 ft. to 11 ft., From ft. to ft.  
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage  
 Direction from well? northwest How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	CLY, V DK BRN, V SNDY, MOIST			
3	10	CLY, YL/BRN, V SLTY, TR SND, DAMP			MW2
10	15	CLY, YL/BRN, SL SLTY, DAMP			SITE ID 00070207
15	20	CLY, LT YL/GY, SL SNDY, DAMP			FLUSH COVER
20	30	CLY, LT YL/GY, TR SND, TR SLT, DAMP			
30	35	CLY, YL/BRN, MOD SNDY, DAMP			
35	38	SHALE, LT TO DK GY/BL, H WTHRED			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-08-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 10-14-93 under the business name of GeoCore Services, Inc. by (signature) *Doug Ray*