

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Rush		SW¹/₄ SW¹/₄ NW¹/₄	34	T 17 S	R 18 E (W)
Distance and direction from nearest town or city street address of well if located within city?					
Northwest corner of 9th Street & Columbia Street					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
LaCrosse Power Plant		221 E. 9th Street			
LaCrosse, Ks.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: NA			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL . . . 8.83 ft. below land surface measured on mo/day/yr 11-03-93			
		Pump test data: Well water was . . . ft. after . . . hours pumping . . . gpm			
		Est. Yield . . . gpm: Well water was . . . ft. after . . . hours pumping . . . gpm			
		Bore Hole Diameter: 7 5/8 in. to 33 ft., and . . . in. to . . . ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes . . . No X . . . If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes . . . No X . . .			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . . . Clamped . . .			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded . . .			
(2) PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded X . . .			
Blank casing diameter . . . 2 in. to 18 ft., Dia . . . in. to . . . ft., Dia . . . in. to . . . ft.		lbs./ft. Wall thickness or gauge No. sch: 40			
Casing height above land surface . . . 0 in., weight . . . lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		(7) PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) . . .		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot (3) Mill slot 5 Gauzed wrapped 6 Wire wrapped 9 Drilled holes		10 Other (specify) . . .			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From . . . 18 ft. to . . . 33 ft., From . . . ft. to . . . ft.					
GRAVEL PACK INTERVALS: From . . . 16 ft. to . . . 33 ft., From . . . ft. to . . . ft.					
6 GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite 4 Other . . .					
Grout Intervals: From . . . 0 ft. to . . . 8 ft., From . . . 8 ft. to . . . 16 ft., From . . . ft. to . . . ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy (11) Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage		60			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? southeast		How many feet?			
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	3	cly, v drk brn, organic rich			
3	6	cly, v lt olv brn, mod-v slty, tr f snd			
6	18	cly, red-brn, mod-v slty, sl snd & grvl szd caliche			
18	24	cly, red-brn, v sndy, v f-med grn, mod caliche			
24	30	snd, v clyey, v f grnd, v slty, yell brn			
30	33	snd, v f grnd, yell-brn, w/red, mod limestone			
MW6-flush mount cover					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . . . 10-21-93 . . . and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. . . . 527 . . . This Water Well Record was completed on (mo/day/yr) . . . 01-03-94 . . . under the business name of GeoCore Services, Inc. by (signature) <i>Don. [Signature]</i>					