

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rush	SW SW 1/4 NW	34	T 17 S	R 18 E (W)

Distance and direction from nearest town or city street address of well if located within city?

Northwest corner of 9th Street & Columbia Street

2 WATER WELL OWNER:	LaCrosse Power Plant	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	221 E. 9th Street	Application Number:
City, State, ZIP Code :	LaCrosse, Ks.	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: NA
	Depth(s) Groundwater Encountered 1. 25 ft. 2. 6.58 ft. 3. 11-03-93 ft.
	WELL'S STATIC WATER LEVEL: 6.58 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was 7 5/8 gpm. Well water was 33 ft. after 7 5/8 hours pumping 7 5/8 gpm
	Est. Yield: 7 5/8 gpm. Well water was 33 ft. after 7 5/8 hours pumping 7 5/8 gpm
	Bore Hole Diameter: 7 5/8 in. to 33 ft. and 33 in. to 33 ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter: 2 in. to 18 ft. Dia			11 Other (specify)
Casing height above land surface: 0 in. weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel	7 Torch cut	10 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 18 ft. to 33 ft.	From 33 ft. to 33 ft.	
GRAVEL PACK INTERVALS:	From 16 ft. to 33 ft.	From 33 ft. to 33 ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 11 ft.	From 11 ft. to 16 ft.	From 16 ft. to 195 ft.	
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? northeast				
How many feet? 195				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	clay, v dk brn, mod slty, organic rich			
3	8	clay, mod brn, mod-v slty, tr calc mat			
8	15	clay, lt red brn, tr v f snd			
15	18	clay, v lt yellowish brn, v sndy, v f-med grn, v slty			
18	24	snd, yell-brn, v f-med grn, v slty & v clayey, tr weath lms			
24	25	snd layer, yell-brn, well srted, med grnd			
25	28	clay, mod-lt brn, v slty & sndy, f-med grnd			
28	33	snd, f-med grnd, sl-mod grvl @ 32', yell-brn			
MW7-flush mount cover					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-22-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 01-03-94 under the business name of GeoCore Services, Inc. by (signature) Dale Kohl
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.