WATER WELL RECORD		Form WWC-5			Division of Water Resources App. No.			
1 LOCATION OF WATER WELL:		Fraction			n Number	Township No.	Range Number	
County: McPherson		NE 1/4 SW 1/4 NE 1/4 NE 1/4			34 T 17 S R 2 □E 🗹 W			
Street/Rural Address of Wel			System (GPS) is					
from nearest town or intersection: If at owner's address, check here .					Latitude: .38.533912 (in decimal degrees)			
5 miles West 1-1/4 mile South of Roxbury, Kansas on 22nd Ave.				Longi	Longitude: 97.521978 (in decimal degrees) Elevation: 1400			
						4, 🗹 NAD 83, 🗀] NAD 27	
2 WATER WELL OWNER: Leland Enckson				Collec	Collection Method:			
RR#, Street Address, Box #: 210 N 2nd St					GPS unit (Make/Model:)			
City, State, ZIP Code : Lindsborg, Kansas 67456					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est, Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40					fL			
SECTION BOX: Dept								
N WELL'S STATIC WATER LEVEL10ft. below land surface measured on mo/day/yr6/29/20								
	Pump test	up test data: Well water wasft. after hours pumping gpm 5-7gpm. Well water wasft. after hours pumping gpm						
EST	gpm. Well water	r was	tt. after hours pumping gpm					
w F Bore Hole Diameter								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted								
· · · · · · · · · · · · · · · · · · ·								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Of Glued Clamped Welded Threaded								
Casing diameter								
Casing height above land surface 12 in., Weight 2.37 lbs/ft., Wall thickness or gauge No. 0.214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)								
		None used (open he	ole)					
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot								
SCREEN-PERFORATED INTERVALS: From								
SCILLIA-I LAG OKATED INT							toft.	
GRAVEL PACK INT	FRVALS: From	. 20	ft to 40	• • • • • • • • • • • • • • • • • • • •	ft From	A	to ft	
GRAVEL PACK INTERVALS: From							to ft	
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other								
Grout Intervals: From 0 ft. to .20 ft., From								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seenage pit ☐ Feedvard ☐ Fertilizer storage ☐ Oil well/gas well								
Direction from well None	within 1/4 mile							
	LITHOLOGIC L	<u>OG</u>	FROM	то	LITHO. LO	OG (cont.) <u>or</u> PLU	JGGING INTERVALS	
0 3 Topsoil						,		
3 10 Clay, tan							W.W.	
	creek gravel							
16 22 Clay								
22 42 Clay w/layer	s of creek grave	el						
				l		*		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, 🗌 reconstructed, or 🗌 plugged								
under my jurisdiction and was completed on (mo/day/year)6/29/2015 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 897 This Water Well Record was completed on (mo/day/year) 6/30/2015								
under the business name ofP.	eterson McNett	Drilling, Inc.		by (si	ignature)	you Monet		
INSTRUCTIONS: Use typewriter or								
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								

http://www.kdheks.gov/waterwell/index.html