


LOCATION OF WATER WELL: Fraction SW 1/4 Section Number 28 Township Number T 17 S Range Number R 22W EW

name and direction from nearest town or city street address of well if located within city?
1/4 N ofazine, Kansas

WATER WELL OWNER: Allan Janice Red Tiger Driller Pavlu #1
 #, St. Address, Box #: azine, Kansas 1720 Ks. State Bank Bldg. Board of Agriculture, Division of Water Resources
 State, ZIP Code: 67516 Wichita, Kansas 67202 Application Number: Unknown

LOCATE WELL'S LOCATION WITHIN "X" IN SECTION BOX:
 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: Unknown
 Depth(s) Groundwater Encountered 1. 9 ft. 2. . ft. 3. . ft.



WELL'S STATIC WATER LEVEL: 9 ft. below land surface measured on mo/day/yr 8/16/82
 Pump test data: Well water was . ft. after . hours pumping . gpm
 Est. Yield: 60 gpm; Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter: 8 IR in. to 38 ft., and . in. to . ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 RVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Casing diameter: 5 in. to 13 ft., Dia. . in. to . ft., Dia. . in. to . ft.
 Setting height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 RVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 13 ft. to 38 ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 38 ft., From . ft. to . ft.

ROUTING MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Routing Intervals: From 0 ft. to 10 ft., From . ft. to . ft.
 If it is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Contamination from well? South How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
14	14	clay			
14	38	Sand and gravel			

Best Available Copy

AUG 30 1982
 BUREAU OF OIL
 ENVIRONMENTAL GEOLOGY

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/16/82 and this record is true to the best of my knowledge and belief. Kansas Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 8/16/82 by the business name of Reddy's Water Well Service by (signature)

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top 2 copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.