

1 LOCATION OF WATER WELL: County: Lane Fraction SE 1/4 Ne 1/4 NE 1/4 Section Number 10 Township Number T 17 S Range Number R 29 EW

Distance and direction from nearest town or city street address of well if located within city?  
From Dighton - 6 1/2 Miles North, 2 Miles West, 3999 Ft. North & 70 Ft. West.

2 WATER WELL OWNER: Lane County Feeders  
RR#, St. Address, Box #: P. O.. Box 607 Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: Dighton, Kansas 67839 Application Number: 38677

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE sections. An 'X' is marked in the NE section.]

4 DEPTH OF COMPLETED WELL: 165 ft. ELEVATION: ...  
Depth(s) Groundwater Encountered 1. 117 ft. 2. ... ft. 3. ... ft.  
WELL'S STATIC WATER LEVEL: 117 ft. below land surface measured on mo/day/yr 10-24-89  
Pump test data: Well water was ... ft. after ... hours pumping ... gpm  
Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm  
Bore Hole Diameter: 30 in. to 165 ft., and ... in. to ... ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes ... No X ...; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped ...  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ...  
7 Fiberglass Threaded ...  
Blank casing diameter: 16 in. to 130 ft., Dia ... in. to ... ft., Dia ... in. to ... ft.  
Casing height above land surface: 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250  
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) ...  
12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ...  
SCREEN-PERFORATED INTERVALS: From 130 ft. to 165 ft., From ... ft. to ... ft.  
GRAVEL PACK INTERVALS: From 20 ft. to 165 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other ...  
Grout Intervals: From 0 ft. to 20 ft., From ... ft. to ... ft.  
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage N/A  
Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-16-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 12-27-89 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4

*The  
Professionals*

**MINTER-WILSON DRILLING CO.**  
INCORPORATED

Irrigation  
and Domestic  
Water Systems  
Complete Installation  
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Lane County Feeders  
Lane County  
10-9-89

Location: NE 1/4 10-17-29

Static Water Level - \_\_\_\_\_

Test #1

0	13	Surface
13	18	Tan sandy clay
18	37	Gypsum
37	53	Tan sandy clay
53	60	Tan sand
60	70	Brown clay
70	79	Small to medium gravel
79	86	Brown clay
86	113	Sand stone
113	126	Medium to coarse gravel
126	128	Clay
128	159	Medium to coarse gravel
159	166	Yellow clay
166	170	Shale

165' T.D. of well