		L RECORD	FORM W	WC-3			r Resources App. No		
			Fraction 1/4 SW 1/4 NW	1 1/2 NNA / 1/2	Section	on Number 4	Township No. T 17 S	Range Number ☐E ☑W	
County: Scott ¼ SW ¼ Street/Rural Address of Well Location; if unknown, distan					Globa	Global Positioning System (GPS) information:			
	from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees)			
Hwy 4 & Taos Rd. 8 Tenths Mile North, 100' East					Longitude: (in decimal degrees)				
TIWY 4 & Taus nu. o Tenths Wille North, Too East					Eleva	Elevation:			
2. WATER WELLOWNER.						<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Garden City Co-Op					Collec	Collection Method:			
RR#, Street Address, Box #: P O Box 838					☐ GPS unit (Make/Model:				
City, State, ZIP Code : Garden C			Citv. KS 67846		Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m				
3 LOCATE WELL									
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 190 ft.									
SECT	SECTION BOX: N Depth(s) Groundwater Encountered (1)								
	WELL'S STATIC WATER LEVEL132'8"ft. below land surface measured on mo/day/yr9/1.1/14								
ا را	Pump test data: Well water was .136ft. after .4 hours pumping .50 gpm								
X N	W N	E n .v. 1 n.	EST. YIELD. 100gpm. Well water was						
W			WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
			Feedlot						
SV	V S	E Irrigation							
			bacteriological sample						
	S		day/yr sample was sub						
	1 mile	Water well disin	fected? ☑ Yes □	No					
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter .5 in. to .160 ft., Diameter ft., Diameter ft.									
Casing height above land surface18 in., Weight 200lbs./ft., Wall thickness or gauge NoSDR21									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
☐ Continuous slot ✓ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)									
SCREEN-PERFORATED INTERVALS: From160									
From									
GRAVEL PACK INTERVALS: From									
From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other									
Grout Intervals: From .5									
What is the nearest source of possible contamination:									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well									
Watertight sewer lines ☐ Seepage pit ☐ Feedyard									
Direction from well North Distance from well .300'									
FROM	ТО	LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
0	2	Top Soil		182	185		y, Few Coarse S	and Small	
2	25	Brown Clay				to Medium	Gravel Streaks		
25	50	Gypsum, Cemented Sa		185	190	Yellow Soa	apstone		
50	70	Fine to Medium Sand, Cemented Str.							
70	85	Brown Clay, Cemented Sand Streaks							
85	105	Cemented Sand, Few Fine Sand Str.						 	
105	124	Brown Clay, Few Small Fine Sand Str							
124	182	Coarse Sand Small Gravel Some							
		Medium Gravel, White Broken Rock							
	(Loose-Clean)								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .9/8/14									
Kansas Water Well Contractor's License No. 532 This Water Well Record was completed on (mo/day/year) 9/19/14									
under the business name ofMidwest Well & Pump Inc									
		Ose typewriter or ball point pen o Kansas Department of Health							
Telephone	785-296-	5522. Send one copy to WAT							
http://www.kdheks.gov/waterwell/index.html									
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									