USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

RUSSELL SPRINGS 35N

WATER WELL RECORD KSA 82a-1201-1215

BDD

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction			Section number		Township number	Range number		
1. Location of well:	Wichita	SE 1/4 SE1/4 NW	1/4	22)	T 17 S	R 37	€ ®	
2. Distance and direction from nearest town or city: $5\frac{1}{2}$, $1\frac{1}{2}$ Of 3. Owner					"IIIaid Raibadii				
Street address of well location if in city: Leoti, KS R.R. or City, st						Leoti, KS 67861			
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. — in. Completion date 9-5-75 Well depth			
N						7Cable toolX Rotary Driven Dug			
						Hollow rod Jetted		se rotary	
						8. Use: X Domestic Public supply Industry			
					Irrigation Air conditioning Stock Lawn Oil field water Other				
SW SE						9. Casing: Material Plast Height: Above or below			
<u> </u>						Threaded Welded Surface 12 in. RMP PVC Weight 1.8 lbs./ft.			
S 1 1 Mile						Dia. 5 in. to 110 ft. depth! Wall Thickness: inches or			
5. Type and color of material				From	То	Dia in. to ft. dept	•		
						10. Screen: Manufacturer's n	& Lowell		
Clay					25	Type Plastic			
Fine sd c	elay			25	32	Slot/gauze110	Length	ft.	
			_		~	ft. a	nd	ft.	
Clay				32	40	Gravel pack? Yes Size ran			
Fine sd c	lay			40	45	11. Static water level: N.	face Date	/day/yr.	
Clay				45	50	12. Pumping level below land			
Rock				50	56	ft. after h		g.p.m.	
				1 50	50	Estimated maximum yield		g.p.m.	
Clay				56	70	13. Water sample submitted: Yes X No [mo./ Date	/day/yr.	
Fine sd clay				20	72	14. Well head completion: NA			
K Sd rock				77	79	Pitless adapter	Inches above g	rade	
				' '	79	15. Well grouted? Bentonite Concrete			
Fine sd				79	83	Depth: FromO ft. toft.			
Clay				83	92	16. Nearest source of possible contamination: None ft Direction Type			
Fine sdy	clay			92	125	Well disinfected upon comple		<u>-</u> ∾ [(
Sd coarse				125	128	17. Pump: Manufacturer's name	X Not installed	17,	
Yellow						Model number	_ HP Volt		
16TTOM				128	145	Length of drop pipe Type:	_ ft. capacity	g.p.m. 🔇	
Shale				145		Submersible	Turbine		
	(Use a second	sheet if needed)				Jet Centrifugal	Reciproc	ating S	
18. Elevation:	19. Remarks: BROCK	,				20. Water well contractor's c	ertification:	, <i>V</i>	
						is true to the best of my knowl	•	· .	
Topography:	3300 (TOPO)				Weishaar Drillin	ig 2	232 × ×	
Slope	7,00					Business name Address Scott Cit	KS 67871	nse No.	
Upland X Valley						Signed Authorized regr	utor part	<u>2-11</u> -75	
	e and pink copies to the Department	of Health and Environment					Form WWC	۱۶۰۰ سبب ۱۶۰۰	