WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | number | Township number | Range number | |
|---|---|---------------------------|---------------------|--|--|--------------------|--------------|
| 1. Location of well: | Wichita | SW 1/4 SW 1/4 SE 1/4 | | 31 | 17 17 5 | R 37 | E Ø |
| 2. Distance and dire | ection from nearest town or city: 4 | .,), 2 02 | wner of wel | l: | M. O. Nuss | | |
| Street address of well location if in city: Leoti, KS R.R. or stre City, state, | | | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | 6. Bore hole dia. 26 in. Completion date | | |
| I N | | | | Well depth 195 ft. 6-19-75 7 Cable tool Rotary Driven Dug | | | |
| * Well | | | | Hollow rod Jetted Bored X_ Reverse rotary | | rse rotary | |
| • | | | | | 8. Use: Domestic I | | |
| * W I I'z mu | | | | | X Irrigation Air conditioning Stock | | |
| SW SE | | | | | 9. Casing: Material Steel Height: Aboy or below | | |
| x Feed | | | | Threaded Welded Surfacein. | | | in. |
| S | | | | | RMPPVCWeight_31_67_lbs./ft. Dia16n_ to 195ft_depth Wall Thickness: inches or | | |
| 1 Mile → 1 5. Type and color of material | | | | То | Diain. toft. de | ` ' 1 | 88 ° |
| .,,, | | | From | | 10. Screen: Manufacturer's | name | |
| Clay | | | | 22 | Type Prime Steel Dia. 16 in. | | |
| a | | | 22 | | (G) gauze | Length | t |
| Cyrp | | | | 31 | Set betweenft. andft. | | |
| Rock H | | | | 35 | Gravel pack? Yes Size range of material 3/42-2 | | |
| Gyp | W. 10. 10. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. | | 35 | 55 | 11. Static water level: 135 ft. below land su | | /day/yr. |
| Clay | | | | 63 | 12 Pumping level below lar | | |
| Sd coarse | | | | 69 | 1166 /L | | |
| | | | | 0,7 | Estimated maximum yield — | 650 | _g.p.m. |
| Sd rock | | | | 77 | 13. Water sample submitted: Yes No | mo., | /day/yr. |
| Clay | | | | 95 | (14.)Well head completion: | | |
| Fine sd clay | | | | 1 04 | Pitless adapter (15.) Well grouted? | Inches above | grade |
| Sd coarse | | | | 116 | With North | Bentonite (| Concrete |
| | | | | 110 | Depth; From II. To | Fo | |
| Fine sd clay | | | | 147 | 16. Negrest source of possible contamination: ft. 7920 Direction SW Type Lot. | | |
| Sd coarse | | | | 158 | Well disinfected upon compl | | No |
| Clay | | | 158 | 170 | 17. Pump: Manufacturer's name West | ern Land Ro | ller 7 |
| • | | | | 4 | Model numberGE | HP <u>40</u> Voli | <u>, 460</u> |
| Fine sd | | | 170 | 175 | Length of drop pipe185 Type: | L ft. capacity 650 | -g.p.m. |
| Clay | | | 175 | 179 | Submersible | X Turbine | 1 1 |
| Fine sd clay (Use a second sheet if needed) | | | | 185 | Jet Centrifugal | Recipro | cating S |
| 18. Elevation: | 19. Remarks: Sd coarse | | 11 <u>79</u> 185 | 192 | 20. Water well contractor's | | ١, ا |
| | Clay yell | OM | 192 | 195 | This well was drilled under n is true to the best of my know | | report (|
| Topography: | Shale | | 195 | | Weishaar Dril | | 32 \$ |
| — Hill | | | | | Business name | Lice | ense No. |
| Slope X Upland | | | | | Address | en lan |] [] |
| Valley | | | | 4 | Authorized re | presentative 7-20- | |
| Forward the white, blu | ue and pink copies to the Department | of Health and Environment | | | • | Form WWy | g-5 \ |