


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NW 1/4 Section Number 26 Township Number T 17 S Range Number R 37 EW
 County: Wichita

Distance and direction from nearest town or city street address of well if located within city?
 5 Miles North of Leoti

2 WATER WELL OWNER: Stewart Whitham
 RR#, St. Address, Box #: Rural Route 2 Box 200 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Leoti KS 67861 Application Number: 2877-D2

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 195 ft. ELEVATION: 3325
 Depth(s) Groundwater Encountered 1. 140 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 140 ft. below land surface measured on mo/day/yr 5/4/95
 Pump test data: Well water was 191 ft. after 3 hours pumping 180 gpm
 Est. Yield 180 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 26 in. to ft. and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X] If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 12 in. to 155 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 155 ft. to 195 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 195 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? west How many feet? 1/4 mile

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	Top Soil and Sandy Clay	164	179	Sand (fine to course) 3' Clay 12
16	32	Cliche	179	180	Clay
32	49	Cliche and Sand	180	187	Yellow Clay
49	65	Sandy Clay and Cliche	187	196	Shale
65	70	Cemented Sand			
70	75	Clay			
75	82	Sand (fine)			
82	93	Sandy Clay and Cemented Sand			
93	98	Sand			
98	107	Sand and Sandy Clay			
107	114	Sand			
114	132	Cemented Sand & Sand & Lt. Clay			
132	147	Sand & Cemented Sand 2			
147	153	Sand (fine) 6			
153	164	Sandy Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/2/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/yr) 5/30/95 under the business name of Tyler Water Well Service by (signature) *Paul Egle*

OFFICE USE ONLY
 T
 R
 EW
 SEC.