

1 LOCATION OF WATER WELL: County: Ellsworth		Fraction: NE 1/4 NE 1/4 NE 1/4		Section Number: 31		Township Number: T 17 S		Range Number: R 9 E/W	
Distance and direction from nearest town or city street address of well if located within city? 530 S & 400' W of NE corner MW-5 OB-63D									
2 WATER WELL OWNER: ENRON									
RR#, St. Address, Box # City, State, ZIP Code: Bushton, KS					Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: 193 ft. ELEVATION: Depth(s) Groundwater Encountered: 1. 62.08 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 62.08 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 12.75 in. to 99 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter: 8 in. to 0-99 ft. Dia. 2 in. to 0-113 ft. Dia. 2 in. to 143-163 ft. Casing height above land surface: 32 in. weight: 69 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 113 ft. to 143 ft. From 163 ft. to 193 ft. From 110 ft. to 198 ft. GRAVEL PACK INTERVALS: From 110 ft. to 198 ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 8 ft. to 106 ft. From 106 ft. to 110 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Unknown How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 54 Silt & Clay 54 65 SS 65 90 Clay/Shale 90 96 SS 96 112 Shale 112 120 Sand 120 135 Clay 135 160 SS 160 195 SS w/ clay stringers 195 198 SS									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-18-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 581 This Water Well Record was completed on (mo/day/yr) 5/10/96 under the business name of Layne, Inc. by (signature) Steve Mitchell									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									