

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ellsworth		SE 1/4 NE 1/4 SE 1/4	31	T 17 S	R 9 E/W
Distance and direction from nearest town or city street address of well if located within city? Approximately 2 1/2 miles south and 2 1/2 west of Lorraine					
2 WATER WELL OWNER:		Enron Gas Processing			
RR#, St. Address, Box # :		Route 1 - Box 5A			
City, State, ZIP Code :		Bushton, KS 67427			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 41 ft. ELEVATION: 1754.07			
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 41.59 ft. below land surface measured on mo/day/yr 11-1-90			
		Pump test data: Well water was not ch'd ft. after hours pumping gpm			
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 9 in. to 39 in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded	
Blank casing diameter 4 in. to 29 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 24 in., weight 1.55 lbs./ft. Wall thickness or gauge No. 173					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		7 PVC 10 Asbestos-cement		11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes		10 Other (specify)	
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 29 ft. to 39 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 29 ft. to 39 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug					
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 27 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well		16 Other (specify below)	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage		13 Insecticide storage saltwater lagoon			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? west How many feet? 500					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 3 Topsoil					
3 6 Brown clay					
6 16 Clay, brown with white rock					
16 30 Clay, brown					
30 36 Dakota sandstone, good, loose, clean					
36 38 Dakota yellow clay					
38 39 Dakota drift					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-7-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 2-20-91 under the business name of Clarke Well & Equipment, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					