

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction <u>SE</u> $\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$		Section Number <u>5</u>	Township Number T <u>18</u> S	Range Number R <u>13</u> E/W
County: <u>Barton</u>						
Distance and direction from nearest town or city street address of well if located within city? <u>473 West 4th St., Hoisington, Ks.</u>						
2 WATER WELL OWNER:		Tom Moore				
RR#, St. Address, Box # :		<u>473 West 4th.</u>				
City, State, ZIP Code :		<u>Hoisington, Ks. 67544</u>				
Board of Agriculture, Division of Water Resources Application Number: <u>BTWW0412</u>						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>60</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr <u>7-3-96</u>				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield <u>na</u> gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter <u>9 7/8</u> in. to <u>60</u> ft. and in. to ft.				
		WELL WATER TO BE USED AS:				
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u>; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes <u>hth</u> No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded				
Blank casing diameter <u>5</u> in. to <u>40</u> ft. Dia. in. to ft. Dia. in. to ft.						
Casing height above land surface <u>2</u> in., weight <u>258</u> lbs./ft. Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 7 <u>PVC</u> 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>60</u> ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>60</u> ft. From ft. to ft.						
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other hole plug Grout intervals: From <u>0</u> ft. to <u>18</u> ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage				
Direction from well? <u>West</u>		How many feet? <u>60</u>				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	3	Top soil				
3	21	Brown clay				
21	40	Sticky brown & gray clay				
40	45	Soft brown clay				
45	50	Broken rock, sand rock, clay				
50	55	Soft yellow brown sandy clay				
55	58	Broken rock sand and clay mixed				
58	60	Fireclay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-3-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>7-12-96</u> under the business name of <u>Rosencrantz-Bemis</u> by (signature) <u>Media Hedson</u>						