


1 LOCATION OF WATER WELL: County: BARTON		Fraction SE ¼ SE ¼ NE ¼	Section Number 5	Township Number T 18 S	Range Number R 13 EW
Distance and direction from nearest town or city street address of well if located within city? 202 N. MAIN, HOISINGTON, KS					
2 WATER WELL OWNER: RICK WEIGER MW-12 RR#, St. Address, Box #: 2208 MCCORMICK City, State, ZIP Code: GREAT BEND, KS 67530 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1837.48 TOC Depth(s) Groundwater Encountered 1. 22 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 20.15 ft. below land surface measured on mo/day/yr 5/16/97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 30 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 30 ft. to 15 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 30 ft. to 14 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 14 ft. to 12 ft., From 12 ft. to 0 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon ☒ Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? NORTH How many feet? 400'					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0.1'	0.2'	BRICK			
0.2'	0.4'	CONCRETE			
0.4'	7'	CLAY - DARK BROWN, SILTY, DRY, NO odor STIFF			
7'	30'	CLAY - BROWN, SILTY, MOIST, STIFF STICKY, NO odor			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/15/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 614 This Water Well Record was completed on (mo/day/yr) 5/30/97 under the business name of MAXIM/KCTL by (signature) <i>William A. Van</i>					