


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton		NW 1/4 NW 1/4 NW 1/4	6	T 18 S	R 13 W
Distance and direction from nearest town or city street address of well if located within city?					
Approx. 1 1/4 mile west of Hoisington					
2 WATER WELL OWNER: Steve Yeakley					
RR#, St. Address, Box #: 467 East Broadway					
City, State, ZIP Code: Hoisington, KS 67544					
Board of Agriculture, Division of Water Resources					
Application Number: not required					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: unknown			
		Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 9-11-84			
		Pump test data: Well water was not ck'd ft. after hours pumping gpm			
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 48 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 5 in. to 30 ft. Dia 5 in. to 48 ft. Dia in. to ft.					
Casing height above land surface 24 in. weight 2.277 lbs./ft. Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)					
9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 3 Mill slot 6 Wire wrapped 9 Drilled holes					
4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 30 ft. to 45 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 26 ft. to 48 ft. From ft. to ft.					
Annular Fill From 10 ft. to 22 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 22 ft. to 26 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? North How many feet? 75					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 25 Topsoil & brown clay some soft sandy water clay					
25 30 Green & blue green clay					
30 45 Soft tan & brown sandy clay & fine sand					
45 48 Brown clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-11-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 9-14-84 under the business name of Clarke Well & EQ., Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4