

1 LOCATION OF WATER WELL: County: Barton		Fraction $\frac{SE}{\frac{1}{4}} \quad NE \quad \frac{1}{4} \quad SE \quad \frac{1}{4}$	Section Number 5	Township Number 18	Range Number 13
Distance and direction from nearest town or city street address of well if located within city? 185' NE of Walnut and Railroad St, Hoisington, KS					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Collingwood Grain P.O. Box 2150 Hoisington, Kansas 67544		Board of Agriculture, Division of Water Resources Application Number: 1830.2	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 25 ft. ELEVATION: 1830.2			
		Depth(s) Groundwater Encountered 1. 15.8 ft. 2. NA ft. 3. 19/94 ft. WELL'S STATIC WATER LEVEL . . . ft. below land surface measured on mo/day/yr . . . Est. Yield . . . gpm; Well water was . . . ft. after . . . hours pumping . . . gpm Bore Hole Diameter . . . in. to . . . ft., and . . . in. to . . . ft. WELL WATER TO BE USED AS: ☐ Public water supply ☒ Air conditioning ☐ Injection well ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☒ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Lawn and garden only ☒ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . . . Clamped . . .			
☒ Steel ☒ PVC Blank casing diameter . . . in. to . . . ft., Dia . . . in. to . . . ft., Dia . . . Sch. 40 Casing height above land surface . . . in., weight . . . lbs./ft. Wall thickness or gauge No.		☐ Wrought iron ☐ Asbestos-Cement ☐ Fiberglass ☐ Concrete tile ☐ Other (specify below)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC			
☐ Steel ☐ Stainless steel ☐ Brass ☐ Galvanized steel SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous slot ☒ Mill slot ☐ Louvered shutter ☐ Key punched		☐ Gauzed wrapped ☐ Wire wrapped ☐ Torch cut ☐ Saw cut ☐ Drilled holes ☐ None used (open hole)			
SCREEN-PERFORATED INTERVALS:		GRAVEL PACK INTERVALS:			
From 10 ft. to 25 ft.		From 8 ft. to 25 ft.			
FROM 0 FT. TO 6 FT.		FROM 6 FT. TO 8 FT.			
6 GROUT MATERIAL:		GROUT INTERVALS:			
☐ Neat cement ☒ Cement grout ☐ Bentonite ☐ Other		From 0 ft. to 6 ft. From 6 ft. to 8 ft.			
What is the nearest source of possible contamination?		How many feet?			
☐ Septic tank ☐ Sewer lines ☐ Watertight sewer lines ☐ Lateral lines ☐ Cess pool ☐ Seepage pit ☐ Pit privy ☐ Sewage lagoon ☐ Feedyard ☐ Livestock pens ☐ Fuel storage ☐ Fertilizer storage ☐ Insecticide storage ☐ Abandoned water well ☒ Oil well/Gas well ☐ Other (specify below)					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Roadgravel & Sand,			MW3
0.5	5	Clay, Medium Brown			GeoCore # 114125 Flush-mount Cover
5	11	Clay, Medium Brown			KDHE # 06005293 Tag # 110204
11	15	Clay, Medium Brown			
15	20	Clay, Medium Brown			
20	25	Clay, Light Gray-Brown			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:					
This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/9/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/9/95 by (signature) Dan Kohl					