

1 LOCATION OF WATER WELL: County: Barton		Fraction: SE 1/4 NE 1/4 SE 1/4		Section Number: 5		Township Number: 18		Range Number: 13		W E/W	
Distance and direction from nearest town or city street address of well if located within city? 125' NNW of Walnut and Railroad St., Hoisington, KS											
2 WATER WELL OWNER: Collingwood Grain		P.O. Box 2150		Board of Agriculture, Division of Water Resources							
RR#, St. Address, Box # :		Hoisington, Kansas 67544		Application Number: 1833.2							
City, State, ZIP Code :											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1833.2									
		Depth(s) Groundwater Encountered 1. 18.7 ft. 2. 20 ft. 3. 19/95 ft. WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield: 8 gpm Well water was 25 ft. after hours pumping gpm Bore Hole Diameter: in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter in. to 10 ft., Dia. in. to ft., Dia. in. to ft. Sch. 40 Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 2 Mill-slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS:		From 10 ft. to 25 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 8 ft. to 25 ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 0 ft. to 6 ft., From 6 ft. to 8 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage 60 Direction from well? NW How many feet?									
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS							
0	0.5	Topsoil, Very Dark			MW2						
0.5	3	Clay, Very Dark Brown			GeoCore # 114125 Flush-mount Cover						
3	5	Clay, Medium Brown			KDHE # 06005293 Tag # 110211						
5	10	Clay, Light Orange-Brown									
10	14	Clay, Medium Orange-Brown									
14	20	Clay, Light Orange Brown									
20	25	Clay, Light Brown									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/9/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/9/95 under the business name of GeoCore Services, Inc. by (signature)											