

1 LOCATION OF WATER WELL: County: Barton		Fraction $\frac{SE}{\frac{1}{4}}$	NE $\frac{1}{4}$	SE $\frac{1}{4}$	Section S	Township T 18 S	Range R 13 W
Distance and direction from nearest town or city street address of well if located within city? 125' ENE of Walnut and Railroad St., Hoisington, KS							
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Collingwood Grain P.O. Box 2150 Hoisington, Kansas 67544					
		Board of Agriculture, Division of Water Resources Application Number: 1829-5					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 20 ft.					
		Depth(s) Groundwater Encountered 1. 15.1 ft. 2. .ft. 3. 1/9/94 .ft. WELL'S STATIC WATER LEVEL .ft. below land surface measured on mo/day/yr Est. Yield gpm: Well water was .ft. after hours pumping gpm Bore Hole Diameter .in. to .ft., and .in. to .ft.					
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded					
Steel PVC		3 RMP (SR) 4 ABS					
Blank casing diameter .in. to 10 ft., Dia.		Casing height above land surface -2.6 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		SCREEN OR PERFORATION OPENINGS ARE:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		10 Gauzed wrapped 8 Saw cut 11 None (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 10 ft. to 25 ft.		From .ft. to .ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 25 ft.		From .ft. to .ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout intervals: From 0 ft. to 6 ft., From 6 ft. to 8 ft., From .ft. to .ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 17 Fuel Storage					
Direction from well? Northwest		How many feet? 60					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0	0.5	Silt, Light Brown			MW1		
0.5	9	Clay, Light orange-brown			GeoCore # 114125	Flush-mount Cover	
9	14	Clay, Medium brown, trace of very dark g			KDHE # 06005293	Tag # 00110143	
14	20	Clay, Light Gray					
20	25	Clay, Light brown					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/9/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/9/95 by (signature) [Signature]							