


1 LOCATION OF WATER WELL: County: Barton		Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 30	Township Number T 18 S	Range Number R 14W E/W
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 S, 2 E of Olmitz, Kansas					
2 WATER WELL OWNER: Joe Schneider RR#, St. Address, Box #: Route 1 City, State, ZIP Code: Olmitz, Ks. 67564 Board of Agriculture, Division of Water Resources Application Number: None					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: Unknown Depth(s) Groundwater Encountered: 43 ft. 2. 8/9/83 ft. 3. 8/9/83 ft. WELL'S STATIC WATER LEVEL: 43 ft. below land surface measured on mo/day/yr Pump test data: Well water was 60 gpm: Well water was 70 ft. after 8 hours pumping 8/9/83 gpm Est. Yield: 60 gpm: Well water was 70 ft. after 8 hours pumping 8/9/83 gpm Bore Hole Diameter: 8 in. to 70 ft., and 70 in. to 70 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter: 5 in. to 50 ft., Dia. 2.8 in. to 50 ft., Dia. 2.8 in. to 50 ft., Dia. 2.8 in. to 50 ft. Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From 50 ft. to 70 ft., From 50 ft. to 70 ft., From 50 ft. to 70 ft. GRAVEL PACK INTERVALS: From 10 ft. to 70 ft., From 10 ft. to 70 ft., From 10 ft. to 70 ft., From 10 ft. to 70 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? East How many feet? 10					
LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 50 Clay 50 70 Sand and Gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/9/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 9/20/83 under the business name of Kellys Water Well Service by (signature) George Ross INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					