

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NE ¼ SE ¼ NW ¼	29	T 18 S	R 15 E/W

Distance and direction from nearest town or city street address of well if located within city?

Located in City of Albert, Street Address not available

2 WATER WELL OWNER:	City of Albert
RR#, St. Address, Box # :	
City, State, ZIP Code :	Albert, KS 67511
	Board of Agriculture, Division of Water Resources
	Application Number: 37,489

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 99 ft. ELEVATION: 1922.75'
	Depth(s) Groundwater Encountered 1. n/a ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL not ck'd ft. below land surface measured on mo/day/yr
	Pump test data: Well water was not ck'd ft. after hours pumping gpm
	Est. Yield 350 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 18 in. to 97 ft. and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped XX
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 8 in. to 72 ft. Dia 8 in. to 84 ft. Dia 8 in. to 97 ft.			Threaded
Casing height above land surface 24 in., weight 5,465 lbs./ft. Wall thickness or gauge No. 332			
TYPE OF SCREEN OR PERFORATION MATERIAL:	XXVXX	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) 060 slot
SCREEN-PERFORATED INTERVALS:	From 72 ft. to 80 ft.	From 84 ft. to 94 ft.	From 97 ft. to ft.
GRAVEL PACK INTERVALS:	From 37 ft. to 97 ft.	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 37 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well?	east			13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				sewage ponds
				How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	38	Topsoil & black & gray clay			
38	58	Sand & gravel, fine to very fine to medium			
58	61	Green clay			
61	66	Sand & gravel, fine to very fine			
66	80	Sand & gravel, fine to med. w/some med. broken limestone cobble			
80	83	Green & black clay			
83	94	Sand & gravel, fine to medium w/ medium cobble			
94	97	Yellow & red Dakota clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/22/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 5/30/86 under the business name of Clarke Well & Equipment, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.