WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: Barton	¼ CSW ¼ SW ¼	29	T 18 S	R 15W E/W

Distance and direction from nearest town or city? In Albert, Kansas City Limits

Street address of well if located within city?

2 WATER WELL OWNER: Lester Koochel
RR#, St. Address, Box # : Albert, Kansas 67511
City, State, ZIP Code :

Board of Agriculture, Division of Water Resources Application Number: None

3 DEPTH OF COMPLETED WELL 60 ft. Bore Hole Diameter 8 in. to 60 ft., and in. to ft.

Well Water to be used as:
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
7 Lawn and garden only 10 Observation well

Well's static water level 23 ft. below land surface measured on August month 9 day 1980 year

Pump Test Data : Well water was ft. after hours pumping gpm
Est. Yield 60 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)
7 Fiberglass

Casing Joints: Glued Clamped
Welded
Threaded

Blank casing dia 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 9 ABS 11 Other (specify) 12 None used (open hole)

Screen or Perforation Openings Are:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)

Screen-Perforation Dia 5 in. to ft., Dia in. to ft., Dia in to ft.
Screen-Perforated Intervals: From 40 ft. to 60 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
Gravel Pack Intervals: From 10 ft. to 60 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)
13 Watertight sewer lines

Direction from well West How many feet 50 ? Water Well Disinfected? Yes No
Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, date sample was submitted month day year: Pump Installed? Yes No
If Yes: Pump Manufacturer's name Model No HP Volts
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on August month 9 day 1980 year, and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186
This Water Well Record was completed on August month 25 day 1980 year under the business name of Kellys Water Well Service by (signature) Kelly Price

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



ELEVATION: Unknown

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	25	Clay			
25	60	Sand and Gravel, with clay streaks			
		AR ≥ 60' 7/m			

Depth(s) Groundwater Encountered 1. 23 ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 18 R 15 EW SEC. 29 C ¼ SW ¼ SW ¼