WATE	VATER WELL RECORD Form WWC-5				Division of Water Resources App. No. 20150342			
		OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
1 -	nty: Rus		1/4 NE 1/4 SE 1/4	NW 1/4	21	T 18 S	R 16 □E ☑W	
		Address of Well Location;			Global Positioning			
	from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)		
1/4 North, 1/2 West of Schaffer							(in decimal degrees)	
, , , , , , , , , , , , , , , , , , ,					Elevation:			
2 WATER WELL OWNER: Duke Drilling					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Duke Drilling RR#, Street Address, Box #: P.O. Box 823					Collection Method: GPS unit (Make/Model:)			
C' C ZZD C 1					Digital Map/Photo, Topographic Map, Land Survey			
City, State, ZIP Code : Great Bend. KS 67530					Est. Accuracy:			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 55 ft.								
SECTION BOX: Depth(s) Groundwater Encountered (1)						ft. ((3) ft.	
	N	WELL'S STAT	C WATER LEVEL ?.	tt.	t. below land surface measured on mo/day/yr. 9-23-15 t. after hours pumping gpm			
1								
N	W I			ft. after hours pumping gpm				
w			Bore Hole Diameter 10 in. to .55 ft., and in. to					
SV	□ Domestic □ Feedlot ☑ Oil field water supply □ Dewatering □ Other (Specify belo □ Irrigation □ Industrial □ Domestic-lawn & garden □ Monitoring well							
Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5 in. to .55 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From ft. to ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 55 ft. to 20 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedvard ☐ Fertilizer storage ☐ Oil well/gas well None							د	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None Direction from well								
FROM	ТО	LITHOLOG		ROM			GGING INTERVALS	
0	3	Top soil		101/1	TO EITHOLE	od (com.) or 1 Be	GOING INTERVALS	
3	24	Brown clay						
24	27	Sand & gravel				-		
27	38	Brown clay			***************************************			
38	46	Gravel- small to med						
46	48	Brown clay						
48	55	White shale						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, \Box reconstructed, or \Box plugged								
under my jurisdiction and was completed on (mo/day/year) .9-23-15								
Kansas V	Water W	ell Contractor's License No	o134 This Wate	r Well Re	cord was completed	on (mo/day/year)	9-28-15	
under the	e busines	ss name of Rosencrantz	- Bemis Entinc		by (signature)	Jora al	e fr	
INSTRUC	ATONS: Kansas Da	Use typewriter or ball point pen.	PLEASE PRESS FIRMLY and pent Rureau of Water Geologic	PRINT clea	rly. Please fill in blanks	and check the correct	inswers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								