

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

|   |  |   |   |  |                                  |                               |
|---|--|---|---|--|----------------------------------|-------------------------------|
| 1. Location of well:  |  | County<br><b>Rush</b>   | Fraction<br><b>SW 1/4 NE 1/4 SE 1/4</b> | Section number<br><b>15</b>  | Township number<br><b>T 18 S</b> | Range number<br><b>R 16 W</b> |
| 2. Distance and direction from nearest town or city:<br><b>4 miles Southwest of Otis, KS</b><br>Street address of well location if in city: |  |   |   | 3. Owner of well: <b>Ed Mohr</b><br>R.R. or street: <b>(?)</b><br>City, state, zip code: <b>Otis, KS 67565</b> |                                  |                               |
| 4. Locate with "X" in section below:<br>N<br>W<br>E<br>S<br>1 Mile<br>1 Mile  |  |   |   | Sketch map:<br>  |                                  |                               |
| 5. Type and color of material   |  |   |   | From   | To                               |                               |
| Top soil, brown silt & brown clay   |  |   |   | 0  | 23                               |                               |
| Sand and gravel with clay streaks   |  |   |   | 23   | 34                               |                               |
| Gray clay   |  |   |   | 34   | 43                               |                               |
| Sand, gravel and thin green clay streaks  |  |   |   | 43   | 60                               |                               |
| Green sandy clay  |  |   |   | 60   | 65                               |                               |
| Sand and coarse gravel with thin clay streaks   |  |   |   | 65   | 76                               |                               |
| Brown sandy clay & green clay   |  |   |   | 76   | 84                               |                               |
| Sand, gravel and clay streaks with 4' of Dakota   |  |   |   |  |                                  |                               |
| Drift   |  |   |   | 84   | 105                              |                               |
| Dakota Clay   |  |   |   | 105  | 106                              |                               |
| BR @ 101' from  |  |   |   |  |                                  |                               |
| (Use a second sheet if needed)  |  |   |   |  |                                  |                               |
| 18. Elevation:  |  | 19. Remarks:<br><b>1930</b>   |   |  |                                  |                               |
| Topography:<br>___ Hill<br>___ Slope<br>___ Upland<br>___ Valley  |  | 20. Water well contractor's certification:<br>This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.<br><b>Clarke Well &amp; Eq., Inc. 185</b><br>Business name License No.<br>Address <b>Great Bend, KS 67530</b><br>Signed <i>[Signature]</i> Date <b>5-17-77</b><br>Authorized representative |   |  |                                  |                               |

6. Bore hole dia. **24** in. Completion date **12-23-77**  
Well depth **106** ft. (Pump Set 5-16-78)

7. \_\_\_ Cable tool \_\_\_ Rotary \_\_\_ Driven \_\_\_ Dug  
\_\_\_ Hollow rod \_\_\_ Jetted \_\_\_ Bored  Reverse rotary

8. Use: \_\_\_ Domestic \_\_\_ Public supply \_\_\_ Industry  
 Irrigation \_\_\_ Air conditioning \_\_\_ Stock  
\_\_\_ Lawn \_\_\_ Oil field water \_\_\_ Other

9. Casing: Material steel Height: Above or below  
Threaded \_\_\_ Welded  Surface 12 in.  
RMP \_\_\_ PVC \_\_\_ Weight 30.3 lbs./ft.  
Dia. 16 in. to 51 ft. depth Wall Thickness: inches or  
Dia. 16 in. to 86 ft. depth gage No. 7 ga.

10. Screen: Manufacturer's name C-Cook  
B-W. A. Brown  
Type Double-slot Dia. 16"  
 Slot gauze 1/8 Length C-30' B-20'  
Set between C- 51 ft. and 61 ft.  
B-61'-81' ft. and C-86'-106' ft.  
Gravel pack?  yes Size range of material 3/8-200

11. Static water level: \_\_\_ mo./day/yr.  
27 ft. below land surface Date **12-23-77**

12. Pumping level below land surfaces: N/C  
\_\_\_ ft. after \_\_\_ hrs. pumping \_\_\_ g.p.m.  
\_\_\_ ft. after \_\_\_ hrs. pumping \_\_\_ g.p.m.  
Estimated maximum yield \_\_\_ g.p.m.

13. Water sample submitted: \_\_\_ mo./day/yr.  
Yes  No Date \_\_\_

14. Well head completion:  
\_\_\_ Pitless adapter 12 Inches above grade

15. Well grouted?  yes  
With:  Neat cement \_\_\_ Bentonite \_\_\_ Concrete  
Depth: From 0 ft. to 10 ft.

16. Nearest source of possible contamination: FIELD  
ft. \_\_\_ Direction \_\_\_ Type \_\_\_  
Well disinfected upon completion? \_\_\_ Yes  No

17. Pump: \_\_\_ Not installed  
Manufacturer's name A. D. Cook (Used)  
Model number \_\_\_ HP \_\_\_ Volts \_\_\_  
Length of drop pipe 70 ft. capacity \_\_\_ g.p.m.  
Type:  
\_\_\_ Submersible  Turbine  
\_\_\_ Jet \_\_\_ Reciprocating  
\_\_\_ Centrifugal \_\_\_ Other

7  
18 16 W  
15  
1/4 1/4 1/4  
SUNSET