

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rush	NE 1/4 NE 1/4 NE 1/4	1	T 18 S	R 17 E <b>(W)</b>

Distance and direction from nearest town or city street address of well if located within city?

101 North Main, Bison, Kansas MW#9

2 WATER WELL OWNER:	Mid-State Coop	Board of Agriculture, Division of Water Resource
RR#, St. Address, Box # :	101 North Main	Application Number:
City, State, ZIP Code :	Bison, Kansas	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 58.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 46 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 44 ft. below land surface measured on mo/day/yr 12-11-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 7.7/8 in. to 58.5 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <input checked="" type="checkbox"/>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<b>2 PVC</b>	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 38.5 ft. Dia in. to ft. Dia in. to ft.			Threaded <input checked="" type="checkbox"/>
Casing height above land surface 24 in. weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<b>7 PVC</b>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<b>3 Mill slot</b>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 38.5 ft. to 58.5 ft. From ft. to ft.		
GRAVEL PACK INTERVALS:	From 36.5 ft. to 58.5 ft. From ft. to ft.		

6 GROUT MATERIAL:	<b>1 Neat cement</b>	2 Cement grout	<b>3 Bentonite</b>	4 Other
Grout Intervals: From 0 ft. to 34.5 ft. From 34.5 ft. to 36.5 ft. From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? north				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? 230

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	clay - dark brown - black			
5	7	medium brown clay			above ground cover
7	15	red brown clay, very silty			
15	35	medium - light brown clay, very silty			KDHE ID # 00092597
35	40	red brown clay, silty			
40	42	silty clay light brown			
42	58.5	silt - light brown with very clayey sand stringers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <b>(1)</b> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-19-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527. This Water Well Record was completed on (mo/day/yr) 12-28-92 under the business name of GeoCore Services, Inc. by (signature) Doug Ray
---