

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Rush		SE 1/4 SE 1/4 SE 1/4	21	T 18 S	R 18 E (V)
Distance and direction from nearest town or city street address of well if located within city? Hwy. 183 & Hwy. 96 Int. Rush Center, KS.					
2 WATER WELL OWNER: Renzoil		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : Hwy 183 & 96		Application Number:			
City, State, ZIP Code : Rush Center, Ks.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 65' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 126' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 20.90' ft. below land surface measured on mo/day/yr 3-18-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 14" in. to 65' ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well for Remediation			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded X			
5 Wrought iron 8 Concrete tile					
6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter 6.50 in. to 20' ft. Dia. in. to ft. Dia. in. to SDR 13 ft.					
Casing height above land surface 1' in. weight lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 65' ft. to 20' ft. From ft. to ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 65' ft. to 18' ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 18' ft. to 16' ft. From 16' ft. to 4' ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? East		How many feet? 60'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Grass-dk brn -blk. clay, firm, dry, earthy odor.			
2	9	Brn clay, dry, tight / w trace amt of caliche, no odor, firm, oxide staining.			
9	22	Lt-med brn silty clay, moist, no odor, friable.			
22	31.50	Gray-lt tan gray sandy silt, wet, soft, no odor.			
31.50	35	Tan-grayish silty sand, wet, fine-very coarse grained, poorly sorted, subrounded qtz, ls.			
		feldspar grains, no odor.			
35	63	Fine-very coarse grained sand, wet, no odor.			
		Cobble layer at 53'.			
63	65'6	Dk gray clayey shale to shale, tight, dry, no odor.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-18-96 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-18-96					
under the business name of JB Environmental Drilling by (signature) James Bueker					