

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Rush		SE 1/4 SE 1/4 SE 1/4		21		T 18 S		R 18 EW	
Distance and direction from nearest town or city street address of well if located within city? Hwy. 183 & Hwy. 96 Int. Rush Center, KS.									
2 WATER WELL OWNER:		Renzoil							
RR#, St. Address, Box #:		Hwy 183 & 96							
City, State, ZIP Code:		Rush Center, Ks.							
		Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 65' ft. ELEVATION: 25' ft.							
		Depth(s) Groundwater Encountered 1. 25' ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 20.86 ft. below land surface measured on mo/day/yr 3-24-96							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 14" in. to 65' ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well for Remediation							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded X							
Blank casing diameter 6.50 in. to 20' ft. Dia		in. to ft. Dia in. to SDR 13 ft.							
Casing height above land surface 1' in. weight		lbs./ft. Wall thickness or gauge No. SCH 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC casing 10 Asbestos-cement							
1 Steel 3 Stainless steel Screen 5 Fiberglass		8 RMP (SR) 11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile		9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot		6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 65' ft. to 20' ft. From ft. to ft.							
		From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 65' ft. to 18' ft. From ft. to ft.							
		From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 18' ft. to 16' ft. From 16' ft. to 4' ft.		ft. From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		How many feet? 160'							
Direction from well? East									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 5.50 Grass-dk-med brn clay, dry, earthy odor, firm to hard, low-no plasticity.									
5.50 12 med brn silty clay w/ caliche stringers, moist to dry, firm, no odor.									
12 20 Brn clayey silt, moist to wet, soft, no odor.									
20 24.50 Dk brn clay, tight, firm, moist, no odor.									
24.50 29.50 Gray brn-gray silty clay, moist to wet, no odor.									
29.50 35 Fine-very coarse grained sand & gravel, wet, no odor, subrounded grains.									
35 64 Fine-very coarse grained sand & gravel, wet, poorly sorted, no odor, ls. rx., feldspar.									
64 65 Blk. tight clayey shale, dry, hard, no odor.									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-14-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-18-96 under the business name of JB Environmental Drilling by (signature) James Bieker									