

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Rush		SE 1/4 SE 1/4 SE 1/4	21	T 18 S	R 18 EW
Distance and direction from nearest town or city street address of well if located within city?					
Hwy. 183 & Hwy. 96 Int. Rush Center, KS.					
2 WATER WELL OWNER: Renzoil		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: Hwy 183 & 96		Application Number:			
City, State, ZIP Code: Rush Center, Ks.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 65' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1.25' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 20.91' ft. below land surface measured on mo/day/yr 3-24-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 14' in. to 65' ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well for Remediation			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel		5 Wrought iron		8 Concrete tile	
2 PVC		6 Asbestos-Cement		9 Other (specify below)	
3 RMP (SR)		7 Fiberglass		Welded	
4 ABS				Threaded X	
Blank casing diameter 6.50 in. to 20' ft. Dia		in. to ft. Dia in. to SDR 13 ft.			
Casing height above land surface 1' in. weight		lbs./ft. Wall thickness or gauge No. SCH 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel		5 Fiberglass		8 RMP (SR)	
2 Brass		6 Concrete tile		9 ABS	
3 Stainless steel				11 Other (specify)	
4 Galvanized steel				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot		3 Mill slot		9 Drilled holes	
2 Louvered shutter		4 Key punched		10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		6 Wire wrapped			
From 65' ft. to 20' ft.		7 Torch cut			
From ft. to ft.		10 Other (specify)			
GRAVEL PACK INTERVALS:		From 65' ft. to 18' ft.			
From ft. to ft.		From ft. to ft.			
From ft. to ft.		From ft. to ft.			
From ft. to ft.		From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 18' ft. to 16' ft.		From 16' ft. to 4' ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank		7 Pit privy		11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines		8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines		9 Feedyard		13 Insecticide storage	
Direction from well? East		How many feet? 175'			
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	5	Grass-dk-med brn clay, dry-moist, hard, no odor.			
5	12	Med brn silty clay, moist, firm, earthy odor.			
12	20	Med brn clayey silt to silt, soft, wet, no odor.			
20	24.50	Dk brn clay, dry to moist, firm to tight,			
24.50	26.50	Gray brn-brn gray silt, wet, soft, no odor.			
26.50	30	Gray sandy clay to sandy silt, wet, very soft,			
30	35	no odor, highly plastic.			
35	63	Gray silty sand to sand w/ gravel, wet, no			
63	65	odor, fine-very coarse sand, poorly sorted.			
		Fine-very coarse sand & gravel, wet, no odor,			
		subrounded, poorly sorted.			
		Blk. shale to clayey shale, dry, hard,			
		tight, no odor, no plasticity.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-19-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-18-96 under the business name of JB Environmental Drilling by (signature) James Bueker					