

1 LOCATION OF WATER WELL: County: Rush	Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 28	Township Number T 18 S	Range Number R 18 EW 1
---	----------------------------------	----------------------	---------------------------	---------------------------

Distance and direction from nearest town or city street address of well if located within city?

Hwy. 183 &amp; Hwy. 96 Int. Rush Center, KS.

2 WATER WELL OWNER: Renzoil RR#, St. Address, Box # : Hwy 183 & 96 City, State, ZIP Code : Rush Center, Ks.	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 65' ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1. 24' ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 21.60 ft. below land surface measured on mo/day/yr 3-28-96

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 14" in. to 65' ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well for Arched

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
------------------------------	----------------	-----------------	------------------------------

1 Steel 3 RMP (SR)

2 PVC 4 ABS

Blank casing diameter 6.50 in. to 20' ft. Dia in. to SDR 13

Casing height above land surface 1' in. weight lbs./ft. Wall thickness or gauge No. SCH 40

7 Fiberglass

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 65' ft. to 20' ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 65' ft. to 18' ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 18' ft. to 16' ft. From 16' ft. to 4' ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy

2 Sewer lines 5 Cess pool 8 Sewage lagoon

3 Watertight sewer lines 6 Seepage pit 9 Feedyard

10 Livestock pens 14 Abandoned water well

11 Fuel storage 15 Oil well/Gas well

12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? Northeast

How many feet? 300'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Grass-ls.rx. gravel roadbase.			
.50	6.75	Med-dk brn clay, tight, dry, friable.			
6.75	15.50	Med brn silty clayw/ caliche stringers, firm.			
15.50	20	Med brn clayey silt, moist to wet, soft.			
20	23.50	Dk-med brn silty clay, firm, moist, earthy odor.			
23.50	25.75	Tan-lt gray brn silty to sandy silt, soft,			
		wet at 24', no odor.			
25.75	35	Gray tan sand, wet, no odor, poorly sorted.			
35	61	Fine-very coarse grained gravelly sand, wet,			
		no odor, subrounded grains of qtz, ls.rx.			
61	65	Lt gray to blk. weathered shaley clay to			
		shale, dry, hard, tight, no odor.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-20-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-18-96 under the business name of JB Environmental Drilling by (signature) James Bieker
--