

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rush	SW 1/4 SE 1/4 SE 1/4	29	T 18 S	R 18 E (W)

Distance and direction from nearest town or city street address of well if located within city?  
 Approximately 1 mile south and 1 1/4 miles west of Rush Center

2 WATER WELL OWNER: Carol J. Reynolds  
 RR#, St. Address, Box # : route 1 - Box 21 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code : Rush Center, KS 67575 Application Number: 16,926

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 61.5 ft. ELEVATION: unknown

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. . ft.

WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 2-7-01

Pump test data: Well water was not checked ft. after hours pumping gpm

Est. Yield unknown gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 30 in. to 60 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes  No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 16 in. to 43 ft., Dia 16 in. to 60 ft., Dia in. to ft.

Casing height above land surface 18 in., weight 16.15 lbs./ft. Wall thickness or gauge No .500

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 43 ft. to 58 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 22 ft. to 60 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 0 ft. to 22 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	Walnut Creek

Direction from well? South How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Topsoil			
4	24	Clay, brown			
24	34	Sand and gravel, fine, medium, some coarse			
34	36	Clay, dark gray			
36	58	Sand and gravel, fine, medium, coarse			
58	60	Clay, gray, red, and yellow			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-7-01 and this record is true to the best of my knowledge and belief.

Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 2-21-01 under the business name of Clarke Well & Equipment, Inc. by (signature)