331 305	140. 0373.	<b>J</b> J			_						G-AAIAI
1 LOCATIO	ON OF WATE	B WELL:		ER WELL RECORD	Form WW			ID No.	mhor	Panga Nu	mbor.
County:	Sa		SE 1/2	SW ½	NW ½	Section Nu 12		Township Nu <b>14</b>		Range Nur R 03	mber W
			town or city street ad					14	S	R 03	VV
5	01 N. Fron	t St. (1	0 ft. east of east	wall, 23 ft north	of fence	)					
2 WATER	WELL OWNE	ER:		partment of H		Environm	ent				
	dress, Box #			ackson Ste 4			В	pard of Agricu	ılture, Divi	sion of Water Re	esources
City, State,	ZIP Code	:		66612-1367			Aı	pplication Nur	nber:		
3 AN "X" II	WELL'S LO	BOX:	4 DEPTH OF	COMPLETED WEL	L	<b>43</b> ft.	ELEVATIO	N:			
	N		Depth(s) Ground	lwater Encountered	1 1	31	ft. 2		ft.	3	ft.
<b>†</b> [				WATER LEVEL							
<b> -</b> -	NW	NE		p test data: Well							
<u> </u>	v	i 1	Est. Yield	gpm: Well	water was		ft. after	г	hours p	umping	gpm
	^-	-	Bore Hole Diame	eter <b>8.5</b> in TO BE USED AS: c 3 Feed lot	. to	43	ft. an	d	in	. to	ft.
1	{\/	SE	WELL WATER 1	TO BE USED AS:	5 Public w	ater supply	8	Air condition	ing 1	1 Injection well 2 Other (Specif	v helow)
	i	SE ;		4 Industrial						2 Other (Opecin	y Delow)
* L						- ,	-		-		
	S		submitted	bacteriological san	npie submitti	ed to Departr	-			, mo/day/yr sam No No	_
5 TYPE O	F BLANK CAS	SING USE		5 Wrought Iron	. 8	Concrete tile				d Clam	
	el		MP (SR)	6 Asbestos-Ce				ASING JOIN	Weld		peu
2 PV		4 AE	. ,	7 Fiberglass						ded Flu	ısh
								D:-	inrea	ided 110	4311
Casing beig	ht shove land	l surface	in. to 33 Flushmount	in weight	0 703	in. to	π.,	Dia		In. to	π.
TYPE OF S	CREEN OR F	PERFORA	TION MATERIAL:	iii., weigin		7 PVC	DS./IL. Wall	10 Asbe	gauge ivo. stos_ceme	Sch.	
1 Ste			ainless steel	5 Fiberglass				11 Other			
2 Bra	ISS	4 G	alvanized steel	6 Concrete tile	•	9 ABS	(0.1)	12 None	used (ope	en hole)	
SCREEN O	R PERFORA		NINGS ARE:	5 (	Gauzed wra	pped	8 9	Saw cut		11 None (ope	n hole)
1 Co	ntinuous slot		3 Mill slot		Wire wrappe			Drilled holes			
	ivered shutter		4 Key punched		Torch cut		10	Other (speci	fy)		
SCREEN-P	ERFORATED	INTERVA	LS: From	33 ft. to		43	. ft. From		ft. t	io	ft.
			From	ft. to		40	ft. From		ft. t	to	ft.
GR	AVEL PACK I	INTERVAL	.S: From	31 ft. to		43					
6 00011			From				ft. From		ft. 1	10	ft.
			eat cement 2		-	3 Bentonite					
Grout Interv	als From	1	ft. to 31	ft. From							
	nearest source ptic tank	ce of possi	ble contamination:	7 04			Livestock p			andoned water	well
	wer lines		4 Lateral lines 5 Cess pool	7 Pit 8 Se	рпуу wage lagoor		Fuel storage Fertilizer st			l well/ Gas well her (specify belo	JW)
	tertight sewe	r lines	6 Seepage pit		edyard		Insecticide		10 00	ner (specify ben	<b>,</b>
Direction fro	om well?				,		many feet?	•			
FROM	то	CODE		LOGIC LOG	FI	ROM T	0	PLU	JGGING II	NTERVALS	
0	16	C1 MI	Silty Clay, mod plasticity, gran	to high	İ						
16	37	ML	Silt, with low p								
		<del> </del> _	Sand, very fine								
			subangular to							~	
37	43	SP	quartz								
	<del> </del>	-				<del></del>					
		-		A							
7 CONTR	ACTOP'S OF	LANDON	NER'S CERTIFICAT	ION: This water	all une (4)		(2) ========			dan may be de dicate	n and
				10N: This water w					_	li li	
				531						dge and belief.	
	Contractor's lusiness name			l Services, In			/ / /		ed on Imo	o/day/yr) 10	-11-05
INSTR	UCTIONS:. PI	ease fill in l	planks and circle the co	rect answers. Send	three copies	by (signature to Kansas De	partment of H	lealth and Env	ironment E	Sureau of Water.	1000 S W
Jackso	n St., Ste. 420	, Topeka, K	ansas 66612-1367. Te	lephone: 913-296-5	545. Send or	e to WATER	WELL OWN	ER and retain of	one for you	r records.	