VATE	R WELI	RECORD Form WWC-5	Division of Water Resources; App. No.
1 LOCATION OF WATER WELL: Fraction			Section Number Township Number Range Number
Coun	ty: Rush	County SE 1/4 SE 1/4 SE 1/4 SE 1/4	21 T 18 S R 18 E/W
Distance and direction from nearest town or city street address of well if Global Positioning Systems (decimal degrees, min. of 4 digit			
locate	ed within c	ity? Intersection of KS Highway 183 & K-96	Latitude: 38.466167
		LL OWNER: Renzoil, Inc.	Longitude: 99.309056
			Elevation:
	State, ZIF		Datum:
		mad. 0000, 110 010-10	Data Collection Method:
	ATE WE	LL'S 4 DEPTH OF COMPLETED WELL	ft.
	ATION	177 7 1/10	
	ELAN "X' LION BO	IN Depth(s) Groundwater Encountered (1)	ft. (2) ft. (3) ft.
SEC	N N	A: WELL'S STATIC WATER LEVEL	below land surface measured on mo/day/yr
		For Vield come: Well water was	ft. after hours pumping gpm ft. after hours pumping gpm
		WELL WATER TO DE LICED AC. 5 Dates	supply 8 Air conditioning Minjection well
w NW	NE		upply 9 Dewatering 12 Other (Specify below)
" -			& garden) 10 Monitoring wellTest Well
,	. '_		e gardon) 10 months were
SW	SE		Department? Yes No; If yes, mo/day/yrs
		Sample was submitted Wa	er well disinfected? Yes No
	S	,	
TYPE	OF CAS	ING USED: 5 Wrought Iron 8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded			
PVC 4 ABS 7 Fiberglass Threaded. Blank casing diameter 1. in. to 59 ft., Diameter 1 in. to 60-61 ft., Diameter in. to ft.			
Blank ca	sing diam	eter 1 in. to 59 ft., Diameter. 1	in. to .60-61 ft., Diameter in. toft.
asing h	eight abov	e land surface in., Weight 2.0	lbs./ft. Wall thickness or guage NoSchedule 40
TYPE O	F SCREE	N OR PERFORATION MATERIAL:	
1.5	Steel		ABS 11 Other (Specify)
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)			
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 59 ft. to 60 ft., From ft. to ft.			
From			
From			
Tion. It is the first the			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0.5 ft. to 58 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify			
2 Sewer lines 5 Cess pool 8 Sewage-lagoon 11 Fuel storage 14 Abandoned water well below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well			
			ny feet?
FROM	TO	LITHOLOGIC LOG FRO	M TO PLUGGING INTERVALS
0	0.5	Concrete	
0.5	35	Silty Clay	
35	61	SAND	
	`		
		·	
7 CONT	RACTO	R'S OR LANDOWNER'S CERTIFICATION. This work	r well was (1) constructed (2) reconstructed or (3) plugged
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/20/09			
Kansas Water Well Contractor's License No. 709 This Water Well Record was completed on (mo/day/year) 2/3/09			
under the business name of Plains Environmental Service by (signature) pro- Kaly			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top			
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone			
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us a			