VATER	WELL RE	CCORD	Form WV	VC-5			r Resources App. N		
		ATER WELL:	Fraction		Section	Number		Range Number	
		ATEK WEEE.	1/4 SW 1/4 SW	1/4 NW 1/4		24	T 18 S	R 18 □E ☑W	
County	ounty: Rush /4 SVV 1/4 SVV 1/4 NVV reet/Rural Address of Well Location; if unknown, distance & direction			direction	Global Positioning System (GPS) information:				
Street/F	Kurai Address	of well Location,	ovener's address check	Latitude: (in decimal degrees)					
	from nearest town or intersection: If at owner's address, check here .					Longitude: (in decimal degrees)			
1/4 No	1/4 North, 2 East of Rush Center					Elevation:			
						Datum: WGS 84, NAD 83, NAD 27			
A XXIATTI	ER WELL O	WNED: Inter Of			Callagt	on Method			
						PS unit (Mal	ke/Model:)	
	Street Address		venue P		Пр	igital Man/Ph	noto. 🗌 Topographi	ic Map, Land Survey	
City, S	State, ZIP Coo	ie : Rush C	enter, Ks 67575		Est. Ac	curacy: \ \	<3 m, ☐ 3-5 m, ☐] 5-15 m,	
	3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 78 ft.								
	AN "X" IN ADEPTH OF COMPLETED WELL 19								
SECTI	ON BOX:	ft below land surface measured on mo/day/yr. 3.64							
	Pump test data: Well water was 99 to after 3.1/2 hours pumping 983 gpm EST. YIELD 983gpm. Well water was 64 ft. after 3.1/2 hours pumping 983 gpm								
NW	NE	EST. YIELD. 9	30gpm. Well water	R was . Y		in	to	.ft.	
W	L. P. Bore Hole Diameter 99								
A _									
CIV	WELL WATER TO BE USED AS. Fubic water supply								
3 W -	SW SE								
		Was a chemical	/bacteriological sample	submitted to	Departr	ment?	Yes MINO		
S If yes, mo/day/yr sample was submitted									
Water well disinfected? ✓ Yes □ No									
5 TYPE	OF CASING	USED: Stee	PV PVC LIC	Threads		• • • • • • • • • • • • • • • • • • • •			
The contract of the contract o									
Casing diameter .16 in. to .78 ft., Diameter in. to ft., Diameter in. to ft., Diameter ft., Diameter									
Casing height above land surface in., Weight 991.79									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
Steel PVC Uniter (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes Note (open hole)									
SCREEN-PERFORATED INTERVALS: From 78 ft. to 58 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 78 ft. to 20 ft., From ft. to ft.									
T Erom II. W ***************************									
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other Grout Intervals: From									
Grout Int	tervals: Fr	om ft. 1	:o ft., From	20	ft. to .!	ft	., From	ft. to	
What is t	he nearest sou	arce of possible con	tamination:				r		
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									
	Watertight sew	er lines 🔲 Seepage	P**	Fertilizer			540 1,011		
Direct	tion from wel					ell	(OC/	LICCING INTERVALS	
FROM	TO	LITHOLO	GIC LOG	FROM	TO	LITHU.	LOG (cont.) or PL	UGGING INTERVALS	
0	34 Clay	y & sandy clay mix	red						
		d & gravel- med,						<u></u>	
76		y & green shale							
	- Join								
-									
	 								
							and the second s		
						1			
	<u> </u>		INTO ADDRESS AND A STATE OF ST	M. Thin	tor wall	was M cons	structed Trecons	structed, or nlugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water wen was of constituted, in reconstituted, in r									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS PRINTED and PARTY Geology Section 1000 SW Jackson St. Suite 420. Topeka, Kansas 66612-1367									
								h constructed well. Visit us a	
Telephone	2 /83-290-3322. Wkdheks gov/wa	terwell/index html	TILK WILL OWNER and						
KSA 82a	http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Deline Copy, Pink Copy								
1707 07g	- 1 - 1 -								