WATER WELL RECORD			Form W	WC-5	Division of Water Resources App. No.			
1 LOC	ATION	OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
Coun	ty: Rush	1	ne ¼ ne ¼ ne	1/4 1/4	2	T 18 S	R 18 □E ☑ W	
Stree	t/Rural A	ddress of Well Location; i	f unknown, distance &	Global Positioning System (GPS) information:				
		own or intersection: If at o		Latitude: (in decimal degrees)				
2 m	2 miles E. on K4 hwy, S on CR270 Rd, 1 1/2 mile, from Lacrosse,					Longitude: (in decimal degrees)		
KS					Elevation:			
					Datum: WGS 84, NAD 83, NAD 27			
" John French				Collection Method: GPS unit (Make/Model:)				
di ni am di i					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City	, State, Z	Bison, K	(S 67520		Est. Accuracy:			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40								
SEC	TION BOX	BOX: Depth(s) Groundwater Encountered (1).20						
	N WELL'S STATIC WATER LEVEL18							
	Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELD. 8gpm. Well water was								
W Bore Hole Diameter 10 in. to .40 ft., and in. to								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
s If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? \[\overline{\mathcal{A}} \] Yes \[\overline{\mathcal{A}} \] No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5 in. to .40 ft., Diameter in. to								
Casing height above land surface. 26 in., Weight 2.91 lbs./ft., Wall thickness or gauge No21								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From 40 ft. to18 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other								
1			_	1	π. το π.,	From	π. toπ.	
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Oil well/gas Oil Oil well/gas Oil Oil Well/gas Well ☐ Oil Well/gas Oil Oil Well/gas Oil Oil Oil Oil Oil Oil Oil								
. —	_	well			from well			
FROM	ТО	LITHOLOG	IC LOG	FROM	TO LITHO. LC	OG (cont.) <u>or</u> PLU	JGGING INTERVALS	
0	20	Top soil						
20	25	Sand						
25	30	Gravel & shale pieces					.,	
30	40	Shale						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .06/14/13 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 0199 This Water Well Record was completed to do day year) 06/1913								
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at								
http://www.kdheks.gov/waterwell/index.html. KSA 822-1212 Check: White Copy, Pink Copy								
K X A X 79	-1717				Uneck: IIWh	ite Copy, Bl	ue Copy, Pink Copy	