WATE	R WE	LL RECORD	Form WWC-5	Division of Water Resources App. No.	
		OF WATER WELL:	Fraction	Section Number Township No. Range Number	
	nty: Rus		N2 1/4 N2 1/4 NW 1/4 NE 1/4		
	<u></u>		f unknown, distance & direction	Global Positioning System (GPS) information:	
·				Latitude: (in decimal degrees)	
			Longitude: (in decimal degrees)  Longitude: (in decimal degrees)		
3/4	South,	3 East of Rush Center		Elevation: (In decimal degrees)	
				Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27	
		ELL OWNER: Wausau	Development Corp	Collection Method:	
		Address, Box #: 2300 H	ighwav 11 North	GPS unit (Make/Model:)	
City	, State, 2	ZIP Code : Laurel, I	MS 39440	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
	***************************************			Est. Accuracy:	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 120 ft.					
		"IN 4 DEPTH OF	COMPLETED WELL 149	ft.	
SEC	TION BO	Depth(s) Ground	lwater Encountered (1)	ft. (2) ft. (3) ft.	
,	well 3 STATIC WATER DEVEL				
	Pump test data: Well water wasft. after hours pumping				
EST. YIELD. WAgpm. Well water wasft. after hours pumping					
W   E   Bore Hole Diameter 10					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SV	SWSE Domestic Feedlot V Oil field water supply Dewatering Other (Specify below)				
Irrigation Industrial Domestic-lawn & garden Monitoring well					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No					
If yes, mo/day/yr sample was submitted					
	I mile	Water well disin	fected? 📝 Yes 🗌 No		
0.004000 7.0044000 7.0044000					
5 TYPE OF CASING USED: Steel V PVC Other					
Cosing diameter 5 in to 120 A Discovery					
Casing diameter 5 in. to .120 ft., Diameter in. to ft., Diameter in. to ft.					
Casing height above land surface					
☐ Steel ☐ Stainless Steel					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter  Key punched  Wire wrapped  Saw cut  Other (specify)					
SCREEN-PERFORATED INTERVALS: From 120 ft. to 80 ft., From ft. to ft.					
From ft to ft From ft to					
GRAVEL PACK INTERVALS: From 120 ft. to .20 ft., From ft. to .ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From					
What is the nearest source of possible contamination:					
Septic tank  Lateral lines Pit privy  Livestock pens Insecticide storage Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well					
Direction from well South Distance from well .75 ft.					
FROM	ТО	LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0	3	Top soil		The state of the s	
3	51	Tan clay			
51	57	Sand & gravel			
57	71	Tan clay			
71	76	Sand & gravel			
<del>76</del>	115	Sandstone/ short streak	re of chalo		
115	120	Gray shale	13 UI SHAIE		
110	120	Cray Stidle			
F CONTROL CHOOLS ON A LANGUAGE					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year). [218:14 and this record is true to the best of my knowledge and belief					
Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/year) 7-29-14					
under the business name of Rosencrantz- Bemis Ent Inc. by (signature)					
133 I RUCTIONS. USE typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check, the correct answers. Send shows and					
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW, Jackson St., Suite 420, Topaka, Vancas 666 to 1267.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					