

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rush	NE 1/4 NW 1/4 NW 1/4	25	T 18 S	R 18 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 2 1/2 miles east of Rush Center

2 WATER WELL OWNER:	John Oborny	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Route 2 - Box 11	Application Number: 16,408 & RH61-01
City, State, ZIP Code :	Rush Center, KS 67575	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 71 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 33 ft. below land surface measured on mo/day/yr 4-14-92 Pump test data: Well water was not ch'd ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 69 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 16 in. to 49 ft. Dia			
Casing height above land surface 24 in. weight 16.15 lbs./ft. Wall thickness or gauge No. 420			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 49 ft. to 69 ft.		
GRAVEL PACK INTERVALS:	From 20 ft. to 69 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 20 ft.			
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				None known
				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	28	Topsoil and clay, brown			
28	32	Sand and gravel, fine to medium			
32	35	Sand and gravel with clay streaks			
35	44	Sand and gravel, medium to fine			
44	46	Sand and gravel, medium to coarse with clay streaks			
46	47	Clay, gray			
47	69	Sand and gravel, medium to coarse with coarse to large limestone cobble with clay, gray streaks at 48' and 54'			
69		Clay, red and white, Dakota			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-14-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 5-1-92 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well &amp; Equipment, Inc.</i>
---