

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Rush		NE 1/4 NW 1/4 NW 1/4	27	T 18 S	R 18 EW
Distance and direction from nearest town or city street address of well if located within city? Rush Center, Ks. GS 45					
2 WATER WELL OWNER: Harley Renz RR#, St. Address, Box #: RR#2, Box 1 City, State, ZIP Code: Rush Center, Ks.					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 29 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 5/8 in. to 35 ft. and in. to ft.			
WELL WATER TO BE USED AS:					
5 Public water supply    8 Air conditioning    11 Injection well 1 Domestic    3 Feedlot    6 Oil field water supply    9 Dewatering    12 Other (Specify below) 2 Irrigation    4 Industrial    7 Lawn and garden only    10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:					
1 Steel    3 RMP (SR)    5 Wrought iron    8 Concrete tile    CASING JOINTS: Glued Clamped 2 PVC    4 ABS    6 Asbestos-Cement    9 Other (specify below)    Welded 7 Fiberglass    Threaded <input checked="" type="checkbox"/>					
Blank casing diameter 2 in. to 20 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel    3 Stainless steel    5 Fiberglass    8 RMP (SR)    11 Other (specify) 2 Brass    4 Galvanized steel    6 Concrete tile    9 ABS    12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot    3 Mill slot    5 Gauzed wrapped    8 Saw cut    11 None (open hole) 2 Louvered shutter    4 Key punched    6 Wire wrapped    9 Drilled holes 7 Torch cut    10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 18 ft. to 35 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement    2 Cement grout    3 Bentonite    4 Other					
Grout Intervals: From 0 ft. to 16 (cement) ft. From 16 ft. to 18 (bent) ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank    4 Lateral lines    7 Pit privy    10 Livestock pens    14 Abandoned water well 2 Sewer lines    5 Cess pool    8 Sewage lagoon    11 Fuel storage    15 Oil well/Gas well 3 Watertight sewer lines    6 Seepage pit    9 Feedyard    12 Fertilizer storage    16 Other (specify below) 13 Insecticide storage					
Direction from well? NW    How many feet? 765					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	silty clay			above ground cover
7	10	silty to sandy clay			KDHE Tag # 00098151
10	18	silty clay			
18	24	silty to sandy clay			
24	28	silty clay			
28	35	sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-18-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/year) 06-03-92 under the business name of GeoCore Services, Inc. by (signature) Dale Kohl					