

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Rush		NW 1/4 NW 1/4 NW 1/4		27		T 18 S		R 18 EW	
Distance and direction from nearest town or city street address of well if located within city?									
SE Corner of US183 & K96, Rush Center, Ks. MW 6									

2 WATER WELL OWNER: Rush Center Oil, Inc.		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # : RR 2, Box 12		Application Number:	
City, State, ZIP Code : Rush Center, Ks. 67575			

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 7 5/8 in. to 38 ft. and in. to
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <input checked="" type="checkbox"/>	
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>	

5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped	
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	
Blank casing diameter .2 in. to 23 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes			
SCREEN-PERFORATED INTERVALS: From 23 ft. to 38 ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 21 ft. to 38 ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL:		4 Other	
1 Neat cement 2 Cement grout 3 Bentonite			
Grout Intervals: From 0 ft. to 17 (cement) ft. From 17 ft. to 21 (bent) ft. From ft. to ft.			
What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
Direction from well? Northeast		How many feet? 10	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Clay, dark brown, silty			
6	15	Clay, greyish black, silty			Flush mount cover KDHE Tag # 00093675
15	30	Clay, greenish grey, silty			
30	38	Sand, black, fine to coarse			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-24-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2-3-92 under the business name of GeoCore Services, Inc. by (signature) Dale R. R.	
--	--