

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Rush		NW 1/4 NW 1/4 NW 1/4		27		T 18 S		R 18 EW	
Distance and direction from nearest town or city street address of well if located within city?									
SE Corner of US183 & K96, Rush Center, Ks. MW 9									
2 WATER WELL OWNER: Rush Center Oil, Inc.									
RR#, St. Address, Box #: RR 2, Box 12 Board of Agriculture, Division of Water Resources									
City, State, ZIP Code: Rush Center, Ks. 67575 Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:									
4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION:									
Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.									
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr									
Pump test data: Well water was ft. after hours pumping gpm									
Est. Yield gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter: 7 5/8 in. to 37 ft. and in. to ft.									
WELL WATER TO BE USED AS:									
5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded									
Blank casing diameter: 2 in. to 22 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface: 0 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 22 ft. to 37 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 37 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 17 (cement) ft. From 17 ft. to 20 (bent) ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? Southwest How many feet? 60									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3" Concrete pad									
3" 15' Clay, brown, silty									
15 24 Clay, brownish grey, silty, very fine sandy									
24 32 Clay, black									
32 37 Sand, black, fine to coarse									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-24-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2-3-92 under the business name of GeoCore Services, Inc. by (signature) Dale Kell									